

Common User Data

Machine Name:	Xerox VersaLink B415 MFP (08:5E:51)
IP Address:	10.61.5.25
Machine Serial Number:	5330005914
Fax Line1:	
Machine URL:	https://10.61.5.25
Machine Activation Date:	Jan 01, 2021 06:34:38
Total Impressions:	187

Machine Profile

Xerox Asset Tag:	
Customer Asset Tag:	
Service Phone Number:	
Customer Support Number:	
Supplies Phone Number:	
System Administrator	System Administrator name not set
Machine Location:	machine location not set
Managed By	
Primary MB Server:	

Machine Hardware

Fax Card:	
Extended Fax Card:	not present
Fax Card Memory Size:	738 MB
Foreign Interface Card:	not present
Device RAM Size:	1984 MB
Device Storage Size:	used=3470MB/total=14004MB (eMMC)
EPC Memory Size:	187 MB
Productivity Kit:	used=83MB/total=0MB (SSD)
Finisher Type:	Simple Catch Tray
Finisher Punch:	None
Finisher Folder:	not present
Multi-feed Detection Kit	Not Installed

General Setup

Remote Services:	Enabled
Remote Software Download:	Enabled
Remote Services Trans. Time:	01:42
Xerox Workplace Cloud	Disabled
E-mail Alerts:	Disabled
Service Plan:	Neutral
Geographic Region:	unknown
GMT Offset:	+05:30
Cloning Installation	Allowed (Encrypted Files Only)
File Sharing	Enabled
JBIG2	Lossless

Energy Saver

Deep Sleep:	Enabled
Energy Saver Mode:	Job Activated
Smart Proximity Sensor	Not Available

Wake on Arrival:  
Sleep on Departure:

Software Versions

Device Software:	122.029.004.19800
Patch Version:	None
Network Controller:	122.029.19800
UI Panel Firmware:	6.3
Marking Engine:	230.307
Document Feeder:	230.307
Finisher:	000.000.000
Fax:	003.021.002
Scanner:	230.307
Machine Upgrades:	Allowed
Last Successful Upgrade:	July 16, 2024 21:51:53

Media Trays

Tray 1:	Plain, White and Letter (8.5 x 11")
Tray 2:	Plain, White and Letter (8.5 x 11")
Tray 3:	Plain, White and x=216mm, y=210mm
Bypass Tray:	Plain, White and Letter (8.5 x 11")

Installed Options

PS:	Installed
Lockdown Security Solution:	Installed

Connectivity

Mobile Workflows

AirPrint Printing:	Enabled
Mopria Printing Discovery:	Enabled
AirPrint / Mopria Scanning	Enabled
Authentication	Disabled

Physical Connections

USB Settings	
Usb Type A Ports	All Enabled
Wired:	
Ethernet MAC Address:	Enabled
Ethernet Speed/Duplex Setting:	e8:4d:ec:08:5e:51
Wireless:	
Wireless MAC Address:	auto
Network Name (SSID):	Disabled
BSSID:	
Security Mode:	
Encryption Algorithm:	
Status:	

Wi-Fi Direct:	Enabled
Wireless Hardware:	Not Installed
Wi-Fi Protected Setup (WPS) Name:	
Access Point (SSID):	
Show Password on Device Touch Screen:	

NFC:	Enabled
iBeacon (Bluetooth®) for AirPrint Di...	Enabled
iBeacon Hardware:	Not Installed
Bluetooth Device Address:	
iBeacon IP Address:	

Protocols

TCP/IPv4:	Enabled
IP Address:	10.61.5.25
Subnet Mask:	255.255.255.0
Router/Gateway:	10.61.5.1
Automatic Addressing:	DHCP
DHCP Server:	10.61.13.223
DHCP Lease Expiration:	Thu May 9 00:06:01 2024
BOOTP Broadcast:	Disabled
Self Assigned Address State:	Enabled
Self Assigned Address:	

TCP/IPv6:	Enabled
Link Local Address:	fe80::ea4d:ecff:fe08:5e51
Use Router Supplied Prefix:	Enabled
Stateless Global Address 1:	::
Stateless Global Address 2:	::
Manual Address:	
DHCP Addressing:	Use DHCP as directed by a router
DHCP Address:	
Default Gateway:	
DUID (DHCP Unique Identifier):	

DNS Settings:	
Requested Host Name:	XXRXE84DEC085E51
Verified Host Name:	
Requested Domain Name:	
Verified Domain Name:	
Multicast DNS:	Enabled
Release DHCP Leases and DNS Registrati...	Disabled
Primary DNS Server:	10.61.7.15
Prefer IPv6 DNS over IPv4:	Enabled

Bonjour:	
Bonjour Printer Name:	Xerox VersaLink B415 MFP (08:5E:51)
HTTP:	Enabled
Force Traffic over Secure Connection (H...	Yes
IPP	Enabled

SNMP	
SNMP v1/v2:	Enabled
SNMP v3:	Enabled
LPR/LPD:	Enabled
Raw IP Printing:	Enabled

LDAP	
LDAP Server 1 Primary LDAP Address:	0.0.0.0:389
LDAP Server 1 Search Directory Root:	
LDAP Server 1 Secure Connection (LDA...	Disabled
LDAP Server 1 Validate Server Certificate...	Disabled

SMTP	
SMTP Server:	10.61.10.8:25
Connect Encryption (TLS):	No Encryption
Validate Server Certificate (TLS):	

## Protocols (cont.)

POP3	
POP3 Server:	0.0.0.0:110
POP3 Secure Connection (TLS):	Disabled
E-mail Address:	
NTP:	Disabled
FTP Client:	Enabled
FTP Client Mode:	Passive
Web Services on Device:	Enabled

## Apps

## Printing

Banner Sheet:	Enabled
Error Sheets:	Enabled
Paper Substitution:	Enabled
Tray Priority:	1,2,3,5
PostScript	Installed
Level:	3
Version:	3021 101
PCL	
Version:	6
Font Name:	Courier
Custom Color Tables	Enabled
Label:	Not Installed

## Embedded Fax:

Fax Line1:	Disabled
Fax Line2:	

## Server Fax:

Repository Protocol:	Enabled
Repository Server:	SMB
Repository Document Path:	10.61.23.93:445
	/

## Workflow Scanning:

	Enabled
--	---------

## Email:

	Enabled
--	---------

## Scan to Mailbox:

Storage Capacity (MB):	Enabled/Displayed
Storage Used (MB):	672 MB
Cleanup of Public Folders:	50 MB
Cleanup of Created Folders:	Enabled
Cleanup Time:	Enabled

## Scan to Home:

	Daily
--	-------

## Scan To:

Cloud Services:	Disabled
-----------------	----------

## Print From:

Saved Jobs for Reprint:	Enabled
-------------------------	---------

Print From USB:	Enabled/Displayed
Print From MailBox:	Disabled
Cloud Services:	Disabled

## Accounting

Accounting Mode:	Disabled
Network Accounting:	None

## Security

## Authentication Configuration

Machine UI Authentication:	Locally on the Device
Home:	Unlocked
Jobs:	Unlocked
Device:	Unlocked
Device Website Authentication:	Locally on the Device
Authorization:	Locally on the Device
Retrieve E-mail from LDAP:	Enabled

## Authentication Server:

	Kerberos
--	----------

## Xerox Secure Access:

	Disabled
--	----------

## Audit Log:

	Enabled
--	---------

## IP Sec:

	Disabled
--	----------

## IP Filtering:

	Disabled
--	----------

## Security Certificates

Machine Certificate:	Signed
----------------------	--------

Root Certificates Installed:	S4
------------------------------	----

## 802.1x:

	Disabled
--	----------

## Job Data Removal:

Scheduled:	Standard
------------	----------

## FIPS 140-3:

	Disabled
--	----------

## TLS:

TLS Hash:	TLS 1.1 and TLS 1.2
-----------	---------------------

## Trellix Embedded Control:

	SHA-1, SHA-256 and above
--	--------------------------