

User Data	
Account Name	Admin
Account Number	12345678
Account ID	987654321
Account Type	Standard
Account Status	Active
Account Expiry Date	2025-12-31
Account Location	Office
Account Contact	John Doe
Account Email	john.doe@company.com
Account Phone	+1 123 456 7890

Profile	
Profile Name	Default
Profile ID	1
Profile Description	Standard profile for office use
Profile Location	Office
Profile Administrator	Admin
Profile Location	Office

Hardware	
Processor	ARM Cortex-A78
RAM	1GB
Flash Memory	16GB
Hard Drive	Not Present
Network Interface	10/100/1000 Ethernet
Wireless Network	802.11ac
Bluetooth	Bluetooth 5.2
NFC	NFC

Services	
Web Services	Enabled
Mobile Services	Enabled
Cloud Services	Enabled
Security Services	Enabled
Management Services	Enabled
Reporting Services	Enabled
Integration Services	Enabled
API Services	Enabled
System Services	Enabled
Network Services	Enabled
Security Services	Enabled
Management Services	Enabled
Reporting Services	Enabled
Integration Services	Enabled
API Services	Enabled
System Services	Enabled

Versions	
Device Version	1.0.0
OS Version	Android 13
App Version	1.0.0
Kernel Version	4.19.0
BIOS Version	1.0.0
Firmware Version	1.0.0
Driver Version	1.0.0
Language Version	English
Region Version	USA
Timezone Version	EST
Locale Version	en-US
System Version	Android 13
Network Version	802.11ac
Security Version	Android 13
Management Version	Android 13
Reporting Version	Android 13
Integration Version	Android 13
API Version	Android 13
System Version	Android 13

Updates	
Last Update	November 11, 2024 21:08:38
Auto Update	Enabled
Update Frequency	Daily
Update Time	00:00:00

Media Tray	
Tray 1	Plain, White (8.5 x 11")
Tray 2	Plain, White (8.5 x 11")
Tray 3	Plain, White (8.5 x 11")
Tray 4	Plain, White (8.5 x 11")
Tray 5	Plain, White (8.5 x 11")
Tray 6	Plain, White (8.5 x 11")

Connectivity

Mobile Workflows	
AirPrint Printing	Enabled
Apple Printing Discovery	Enabled
Universal Print	Enabled
Universal Print Registration Status	Not Registered
Physical Connections	
USB Settings	
USB Type A Ports	All Enabled
USB Type B Port	Enabled
Connection Timeout	30 seconds
Wired	
Ethernet MAC Address	00:03:4e:fc:36:4b
Ethernet Speed/Duplex Setting	Auto
Wireless	
Wireless MAC Address	00:03:4e:fc:36:4b
Network Name (SSID)	Not Set
BSSID	Not Set
Security Mode	Not Set
Encryption Algorithm	Not Set
Status	Not Set
Wi-Fi Direct	
Wireless Hardware	Enabled
Wi-Fi Protected Setup (WPS) Name	Not Installed
Connection Method	Not Set
Subnet Prefix Address	Not Set
Access Point (SSID)	Not Set
Show Password on Device Touch Screen	Not Set
NFC	
iBeacon (Bluetooth®) for AirPrint Discovery	Enabled
iBeacon Hardware	Not Installed
Bluetooth Device Address	Not Set
iBeacon IP Address	Not Set

Protocols

TCP/IPV4:	
IP Address	0.0.0.0
Subnet Mask	0.0.0.0
Router/Gateway	0.0.0.0
Automatic Addressing	Enabled
DHCP Server	0.0.0.0
DHCP Lease Expiration	Not Set
BOOTP Broadcast	Enabled
Self Assigned Address State	Enabled
Self Assigned Address	Not Set
TCP/IPV6:	
Link Local Address	fe80::9e93:4eff:fc36:4b
Use Router Supplied Prefix	Enabled
Stateless Global Address 1	2001::1
Stateless Global Address 2	Not Set
Manual Address	Not Set
DHCP Addressing	Use DHCP as directed by a router
DHCP Address	Not Set
Default Gateway	2001::1
DUID (DHCP Unique Identifier)	Not Set
DNS Settings:	
Requested Host Name	VERI9C934EFC364B
Verified Host Name	Not Set
Requested Domain Name	Not Set
Verified Domain Name	Not Set
Multicast DNS	Enabled
Release DHCP Leases and DNS Registrations	Enabled
Primary DNS Server	0.0.0.0
Alternate DNS Server 1	0.0.0.0
Alternate DNS Server 2	0.0.0.0
DNS Connection Timeout	5 seconds
Append Device Domain	Enabled
Append Parent Domains	Enabled
DNS Domain Search List	XEROXQA.COM
Prefer IPv6 DNS over IPv4	Enabled

Installed Options

PS	Installed
----	-----------

Protocols (cont.)

Bonjour:	
Bonjour Printer Name:	Xerox VersaLink C620 (FC364)
HTTP:	
Port Number:	80
Force Traffic over Secure Connection (L...):	Yes
Secure HTTP Port Number:	443
Proxy Server:	Manual
Proxy Server Address:	10.177.8.91:8080
IPP:	Enabled
Secure IPP Mode:	IPP over Secure IPPS
IPP Network Path:	http://10.61.16.78:631
SNMP	
SNMP v1/v2:	Enabled
SNMP v3:	Disabled
LPR/LPD:	
Port Number:	515
PDL Switching:	Disabled
PDL Banner Override:	Disabled
Raw IP Printing:	
Port Number 1:	9100
Bidirectional:	Disabled
End of Job Timeout:	300
PDL Switching:	Disabled
LDAP	
LDAP Server 1 Friendly Name:	
LDAP Server 1 Primary LDAP Address:	0.0.0.0:389
LDAP Server 1 Alternate LDAP Address:	0.0.0.0:389
LDAP Server 1 Search Directory Root:	
LDAP Server 1 Secure Connection (LDA...):	Disabled
LDAP Server 1 Validate Server Certificate...:	Disabled
SMTP	
SMTP Server:	0.0.0.0:25
Connect Encryption (TLS):	No Encryption
Validate Server Certificate (TLS):	
Max Message Size (KB):	10240
Number of Fragments:	1
Total Job Size (KB):	300000
Job Splitting Boundary:	Page boundary
Credentials for Auto E-mails:	None
POP3	
POP3 Server:	0.0.0.0:110
POP3 Secure Connection (TLS):	Disabled
E-mail Address:	
Receipt of E-mail via POP3:	Disabled
Send Confirmation Request:	Enabled
Incoming E-mail cover sheet:	Enabled
NTP:	
Primary Server:	0.0.0.0:123
Alternate Server:	0.0.0.0:123
SLP:	
SLP Client:	Enabled
FTP Client Mode:	Passive
Web Services on Device:	
WS-Discovery:	Enabled
WS-Discovery Multicast:	Enabled
WS-Print:	Enabled
Web Services	
Digital Certificate Management and S...:	Enabled
Extensible Service Registration:	Enabled
Job Limits:	Enabled
Job Management Extensions:	Enabled
Device Configuration:	Enabled
Session Data:	Enabled
User Interface Configuration:	Enabled
EIP Proxy Configuration:	Enabled
Xerox Secure Access:	Disabled
EIP SNMP Configuration:	Enabled
Print Submission:	Enabled
Mass Storage Access:	Enabled
Card Reader Access:	Enabled
Authentication & Accounting Configur...:	Enabled
Export Audit Log:	Enabled
Trellix Embedded Control:	Enabled

Apps

Printing

Banner Sheet:	Disabled
Sys/Start Job:	Disabled
Delete Held Jobs After:	3 Day(s) 0 Hour(s) 0 Min(s)
Error Sheets:	Enabled
Paper Substitution:	Enabled
Tray Priority:	1,2,3,4,5,6
Default Copies:	1
Default Job Type:	Normal Print
Default Paper Size:	A x 8.50 inch (A), 11.00 inch (L)
Default Paper Color:	White
Default 2 Sided Printing:	1 Sided
Default Output Tray:	Center Tray
Default Output Color:	Color
Default Collated Sets:	Enabled
Default Stapling:	Not Available
Offsetting Between Jobs:	No Offset Between Jobs
Archival Marking Mode:	Off
PostScript Level:	Installed 3
Version:	3021.101
Image Quality:	Enhanced
PCL	
Version:	6
Pitch Size:	10.00
Point Size:	12.00
Font Name:	Courier
Line Per Page:	60
Custom Color Tables Label:	Enabled
Label:	Not Installed
Print From:	Enabled
Saved Jobs for Reprint:	Enabled
Print From USB:	Enabled
Cloud Services:	Disabled

