

Common User Data

Machine Name: Xerox VersaLink C625 Color MFP (FC:2...
 IP Address: 10.61.16.25
 Machine Serial Number: 5322480450
 Fax Line1: 3337
 Machine URL: https://10.61.16.25
 Machine Activation Date: Nov 12, 2024 13:47:56
 Black Impressions: 7001
 Color Impressions: 4628
 Total Impressions: 11629

Machine Profile

Xerox Asset Tag:
 Customer Asset Tag: XEROX
 Service Phone Number: Carroll
 Customer Support Number:
 Supplies Phone Number:
 System Administrator: System Administrator name not set
 Machine Location: machine location not set

Managed By

Primary MB Server:

Machine Hardware

Fax Card: Embedded; 1 Line
 Fax Memory Size: 738 MB
 Foreign Interface Card: not present
 Device RAM Size: 3904 MB
 Device Storage Size: used=3160MB/total=14004MB (eMMC)
 EPC Memory Size: 187 MB
 Productivity Kit: Not Installed
 Finisher Type: Simple Catch Tray
 Finisher Punch: None
 Finisher Folder: not present
 Multi-feed Detection Kit: Not Installed

General Setup

Remote Services: Enabled
 Remote Software Download: Enabled
 Remote Services Trans. Time: 21:44
 Xerox Workplace Cloud: Enabled
 E-mail Alerts: Disabled
 Service Plan: Plan Activated
 Geographic Region: unknown
 GMT Offset: +05:30
 Cloning Installation: Allowed (Encrypted Files Only)
 File Sharing: Enabled
 JBIG2: Lossless

Energy Saver

Deep Sleep: Enabled
 Energy Saver Mode: Job Activated
Smart Proximity Sensor
 Wake on Arrival: Not Available
 Sleep on Departure:

Software Versions

Device Software: 122.024.004.31210
 Patch Version: None
 Network Controller: 122.024.31210
 UI Panel Firmware: 6.2
 Marking Engine: 230.314
 Document Feeder: 230.314
 Finisher: 000.000.000
 Fax: 003.021.010
 Scanner: 230.314
Machine Upgrades: Allowed
 Last Successful Upgrade: November 11, 2024 12:52:21

Media Trays

Tray 1: Plain, White and A4 (210 x 297 mm)
 Tray 2: Plain, White and Letter (8.5 x 11")
 Tray 3: Plain, White and A4 (210 x 297 mm)
 Tray 4: Plain, White and A4 (210 x 297 mm)
 Tray 5: Plain, White and A4 (210 x 297 mm)
 Bypass Tray: Plain, White and Letter (8.5 x 11")

Installed Options

PS: Installed

Connectivity

Mobile Workflows

AirPrint Printing: Enabled
 Mopria Printing Discovery: Enabled
 AirPrint / Mopria Scanning Authentication: Disabled

Physical Connections

USB Settings
 USB Type A Ports: All Enabled
 USB Type B Port: Enabled → Enabled

Wired:
 Ethernet MAC Address: 78:8c:77:fc:24:43
 Ethernet Speed/Duplex Setting: auto
Wireless:
 Wireless MAC Address:
 Network Name (SSID):
 BSSID:
 Security Mode:
 Encryption Algorithm:
 Status:
 Wi-Fi Direct: Enabled
 Wireless Hardware: Not Installed

Wi-Fi Protected Setup (WPS) Name:
 Access Point (SSID):
 Show Password on Device Touch Screen:
NFC:
 iBeacon (Bluetooth®) for AirPrint Di...: Enabled
 iBeacon Hardware: Not Installed
 Bluetooth Device Address:
 iBeacon IP Address:

Protocols

TCP/IPv4:

Enabled
 IP Address: 10.61.16.25
 Subnet Mask: 255.255.255.0
 Router/Gateway: 10.61.16.1
 Automatic Addressing: DHCP
 DHCP Server: 10.61.13.223
 DHCP Lease Expiration: Mon Nov 25 12:00:18 2024
 BOOTP Broadcast: Disabled
 Self Assigned Address State: Enabled
 Self Assigned Address:

TCP/IPv6:

Enabled
 Link Local Address: fe80::7a8c:77ff:fe7c:2443
 Use Router Supplied Prefix: Enabled
 Stateless Global Address 1: fd00:0:2:116:7a8c:77ff:fe7c:2443
 Stateless Global Address 2:
 Manual Address:
 DHCP Addressing: Use DHCP as directed by a router
 DHCP Address:
 Default Gateway: fe80::8afc:5dff:fe75:e282
 DUID (DHCP Unique Identifier):

DNS Settings:

Requested Host Name: XRX788C77FC2443
 Verified Host Name:
 Requested Domain Name:
 Verified Domain Name:
 Multicast DNS: Enabled
 Release DHCP Leases and DNS Registrati...: Disabled
 Primary DNS Server: 10.61.7.15
 Prefer IPv6 DNS over IPv4: Enabled

Bonjour:

Bonjour Printer Name: Xerox VersaLink C625 Color MFP (FC:2...

HTTP:

Force Traffic over Secure Connection (H...: Yes
 IPP: Enabled

SNMP

SNMP v1/v2: Enabled
 SNMP v3: Disabled

LPR/LPD:

Enabled

Raw IP Printing:

Enabled

LDAP

LDAP Server 1 Primary LDAP Address: 0.0.0.0:389
 LDAP Server 1 Search Directory Root:
 LDAP Server 1 Secure Connection (LDA...: Disabled
 LDAP Server 1 Validate Server Certificate...: Disabled

SMTP

SMTP Server: 10.61.10.8:25
 Connect Encryption (TLS): No Encryption
 Validate Server Certificate (TLS):

Protocols (cont.)

POP3	
POP3 Server:	0.0.0.0:110
POP3 Secure Connection (TLS):	Disabled
E-mail Address:	
NTP:	Enabled
FTP Client:	Enabled
FTP Client Mode:	Passive
Web Services on Device:	Enabled

Apps

Printing

Banner Sheet:	Enabled
Error Sheets:	Enabled
Paper Substitution:	Enabled
Tray Priority:	1,2,3,4,5,6
Archival Marking Mode	Off
PostScript	Installed
Level:	3
Version:	3021.101

PCL

Version:	6
Font Name:	Courier

Custom Color Tables

Label:	Not Installed
--------	---------------

Fax:

Enabled/Displayed	
Fax Line1:	3337
Fax Line2:	

Server Fax:

Enabled	
Repository Protocol:	SMB
Repository Server:	0.0.0.0
Repository Document Path:	

Workflow Scanning:

Enabled

Email:

Enabled

Scan to Mailbox:

Enabled/Displayed

Storage Capacity (MB):	672 MB
Storage Used (MB):	122 MB
Cleanup of Public Folders:	Enabled
Cleanup of Created Folders:	Enabled
Cleanup Time:	Daily

Scan to Home:

Disabled

Scan To:

Enabled

Cloud Services:

Disabled

Print From:

Enabled

Saved Jobs for Reprint:

Enabled

Print From USB:

Enabled

Print From MailBox:

Disabled

Cloud Services:

Disabled

Accounting

Accounting Mode:	None
Network Accounting:	Disabled

Security

Authentication Configuration

Machine UI Authentication:	Locally on the Device
Home:	Unlocked
Jobs:	Unlocked
Device:	Unlocked

Device Website Authentication:	Locally on the Device
Authorization:	Locally on the Device

Retrieve E-mail from LDAP: Enabled

Authentication Server:

Disabled

Xerox Secure Access:

Disabled

Audit Log:

Enabled

IP Sec:

Disabled

IP Filtering:

Disabled

Security Certificates

Machine Certificate:	Signed
Root Certificates Installed:	55

802.1x:

Disabled

Job Data Removal:

Scheduled:	Disabled
------------	----------

FIPS 140-3:

Disabled

TLS:

TLS 1.2 and TLS 1.3

TLS Hash:	SHA-1, SHA-256 and above
-----------	--------------------------

Trellix Embedded Control:

Disabled