

Common User Data

Machine Name: Xerox VersaLink B415 MFP (DC:B8:44)  
IP Address: 10.61.16.24  
Machine Serial Number: 5330005345  
Fax Line1: 3337  
Machine URL: https://10.61.16.24  
Machine Activation Date: Dec 11, 2024 18:40:42  
Total Impressions: 4221

Machine Profile

Xerox Asset Tag:  
Customer Asset Tag:  
Service Phone Number:  
Customer Support Number: 2e12e12e12  
Supplies Phone Number:  
System Administrator: System Administrator name not set  
Machine Location: machine location not set  
Managed By:  
Primary MB Server:

Machine Hardware

Fax Card: Embedded; 1 Line  
Fax Memory Size: 738 MB  
Foreign Interface Card: not present  
Device RAM Size: 1984 MB  
Device Storage Size: used=3056MB/total=14004MB (eMMC)  
EPC Memory Size: 187 MB  
Productivity Kit: Not Installed  
Finisher Type: Simple Catch Tray  
Finisher Punch: None  
Finisher Folder: not present  
Multi-feed Detection Kit: Not Installed

General Setup

Remote Services: Enabled  
Remote Software Download: Enabled  
Remote Services Trans. Time: 08:31  
Xerox Workplace Cloud: Enabled  
E-mail Alerts: Disabled  
Service Plan: Plan Activated  
Geographic Region: unknown  
Startup Config Report: Enabled  
GMT Offset: +05:30  
Cloning Installation: Allowed (Encrypted Files Only)  
Allow Print Submission of Clone Files: Disabled  
File Sharing: Enabled  
JBIG2: Lossless

Energy Saver

Deep Sleep: Enabled  
Energy Saver Mode: Job Activated  
Sleep Mode Timer: 60 minutes  
Auto-Off: Disabled

Software Versions

Device Software: 122.029.005.00800  
Patch Version: None  
Network Controller: 122.029.00800  
UI Panel Firmware: 6.2  
User Interface: 122.029.00800  
Marking Engine: 230.318  
Copy Controller: 122.029.00800  
Document Feeder: 230.318  
Finisher: 000.000.000  
Fax: 003.021.012  
OS: 230.318  
Scanner: 230.318  
Software Upgrade: 005.008  
ALTB00T Software Upgrade: 005.008

Tray 2: A19.1\_B3.1  
Tray 3: A19.1\_B3.1  
Tray 4: A19.1\_B3.1

Machine Upgrades:

Last Successful Upgrade: January 11, 2025 12:20:36  
Scheduled Auto Upgrades: Disabled  
Auto Upgrade Start Time: Daily  
Auto Upgrade Server: 0.0.0.0:21

Media Trays

Tray 1: Plain, White and Letter (8.5 x 11")  
Tray 2: Plain, White and A4 (210 x 297 mm)  
Tray 3: Plain, White and Letter (8.5 x 11")  
Tray 4: Plain, White and Letter (8.5 x 11")  
Bypass Tray: Plain, White and A4 (210 x 297 mm)

Connectivity

Mobile Workflows

AirPrint Printing: Enabled  
Mopria Printing Discovery: Enabled  
AirPrint / Mopria Scanning Authentication: Enabled  
Universal Print: Disabled  
Universal Print Registration Status: Disabled  
Not Registered

Physical Connections

USB Settings  
USB Type A Ports: All Enabled  
USB Type B Port: Enabled  
Connection Timeout: 5 seconds  
Wired: Enabled  
Ethernet MAC Address: 78:8c:77:dc:b8:44  
Ethernet Speed/Duplex Setting: auto  
Wireless: Disabled  
Wireless MAC Address:  
Network Name (SSID):  
BSSID:  
Security Mode:  
Encryption Algorithm:  
Status:

Wi-Fi Direct: Enabled  
Wireless Hardware: Not Installed  
Wi-Fi Protected Setup (WPS) Name:  
Connection Method:  
Subnet Prefix Address:  
Access Point (SSID):  
Show Password on Device Touch Screen:

NFC: Enabled  
iBeacon (Bluetooth®) for AirPrint Di...: Enabled  
iBeacon Hardware: Not Installed  
Bluetooth Device Address:  
iBeacon IP Address:

Protocols

TCP/IPv4:

IP Address: 10.61.16.24  
Subnet Mask: 255.255.255.0  
Router/Gateway: 10.61.16.1  
Automatic Addressing: DHCP  
DHCP Server: 10.61.13.223  
DHCP Lease Expiration: Fri Jan 24 17:48:08 2025  
BOOTP Broadcast: Disabled  
Self Assigned Address State: Enabled  
Self Assigned Address:

TCP/IPv6:

Link Local Address: Enabled  
fe80::7a8c:77ff:fedc:b844  
Use Router Supplied Prefix: Enabled  
Stateless Global Address 1: fd00:0:2:116:7a8c:77ff:fedc:b844  
Stateless Global Address 2: ::  
Manual Address:  
DHCP Addressing: Use DHCP as directed by a router  
DHCP Address:  
Default Gateway: fe80::8afc:5dff:fe75:e282  
DUID (DHCP Unique Identifier):

DNS Settings:

Requested Host Name: XRX788C77DCB844  
Verified Host Name:  
Requested Domain Name:  
Verified Domain Name:  
Multicast DNS: Enabled  
Release DHCP Leases and DNS Registration: Disabled  
Primary DNS Server: 10.61.7.15  
Alternate DNS Server 1: 10.61.10.6  
Alternate DNS Server 2: ::  
DNS Connection Timeout: 5  
Append Device Domain: Enabled  
Append Parent Domain: Disabled  
DNS Domain Search List: XEROXQA.COM  
Prefer IPv6 DNS over IPv4: Enabled

Installed Options

PS: Installed

## Protocols (cont.)

Bonjour:	
Bonjour Printer Name:	Xerox VersaLink B415 MFP (DC:88:44)
HTTP:	Enabled
Port Number:	80
Force Traffic over Secure Connection (H...):	Yes
Secure HTTP Port Number:	443
Proxy Server:	Automatic
Proxy Server Address:	0.0.0.0:8080
IPP:	Enabled
Secure IPP Mode:	IPP and Secure IPPS
IPP Network Path:	http://10.61.16.24:631
SNMP:	
SNMP v1/v2:	Enabled
SNMP v3:	Disabled
LPR/LPD:	Enabled
Port Number:	515
PDL Switching:	Disabled
PDL Banner Override:	Disabled
Raw IP Printing:	Enabled
Port Number 1:	9100
Bidirectional:	Disabled
End of Job Timeout:	300
PDL Switching:	Disabled
LDAP:	
LDAP Server 1 Friendly Name:	
LDAP Server 1 Primary LDAP Address:	0.0.0.0:389
LDAP Server 1 Alternate LDAP Address:	0.0.0.0:389
LDAP Server 1 Search Directory Root:	
LDAP Server 1 Secure Connection (LDA...):	Disabled
LDAP Server 1 Validate Server Certificate...:	Disabled
SMTP:	
SMTP Server:	10.61.10.8:25
Connect Encryption (TLS):	No Encryption
Validate Server Certificate (TLS):	
Max Message Size (KB):	10240
Number of Fragments:	1
Total Job Size (KB):	300000
Job Splitting Boundary:	Page Boundary
Credentials for Auto E-mails:	None
Credentials for Walkup User:	None
POP3:	
POP3 Server:	0.0.0.0:110
POP3 Secure Connection (TLS):	Disabled
E-mail Address:	
Receipt of E-mail via POP3:	Disabled
Send Confirmation Request:	Enabled
Incoming E-mail cover sheet:	Enabled
NTP:	
Primary Server:	0.0.0.0:123
Alternate Server:	0.0.0.0:123
SLP:	Disabled
FTP Client:	Enabled
FTP Client Mode:	Passive
Web Services on Device:	Enabled
WS-Discovery:	Enabled
WS-Discovery Multicast:	Enabled
WS-Print:	Enabled
WS-Scan:	Enabled
Web Services:	
Copy Submission:	Enabled
Digital Certificate Management and Securi...:	Enabled
Extensible Service Registration:	Enabled
Job Limits:	Enabled
Job Management Extension:	Enabled
Device Configuration:	Enabled
Scan Submission:	Enabled
Scan Workflow Management:	Enabled
Session Data:	Enabled
User Interface Configuration:	Enabled
EIP Proxy Configuration:	Enabled
Xerox Secure Access:	Disabled
EIP SNMP Configuration:	Enabled
Print Submission:	Enabled
Scan Template Mgmt:	Enabled
Mass Storage Access:	Enabled
Card Reader Access:	Enabled
Authentication & Accounting Configur...:	Enabled
Export Audit Log:	Enabled
Trellix Embedded Control:	Enabled

## Apps

## Printing

Banner Sheet:	Enabled
Sys/Start Job:	Disabled
Delete Held Jobs After:	3 Day(s) 0 Hour(s) 0 Minute(s)
Error Sheets:	Enabled
Paper Substitution:	Enabled
Tray Priority:	1,2,3,4,5
Default Copies:	1
Default Job Type:	Normal Print
Default Paper Size:	x=8.50 inches, y=11.00 inches
Default Paper Color:	White
Default 2 Sided Printing:	2 Sided
Default Output Tray:	Center Tray
Default Output Color:	Black & White
Default Collated Sets:	Enabled
Default Stapling:	Not Available
Offsetting Between Jobs:	Offset Between Jobs
Archival Marking Mode:	Off
PostScript:	Installed
Level:	3
Version:	3021.101
Image Quality:	Enhanced

## PCL

Version:	6
Pitch Size:	10.00
Point Size:	12.00
Font Name:	Courier
Lines Per Page:	60
Custom Color Tables:	Enabled
Label:	Not Installed
Fax:	Enabled/Displayed
Fax Line1:	3337
Fax Line2:	

## Server Fax:

Confirmation Sheet:	Enabled
Delay Start:	Errors Only
Repository Protocol:	Disabled
Repository Server:	SMB
Repository Document Path:	10.61.23.93:445

## Workflow Scanning:

Confirmation Sheet:	Enabled
Default Repository Protocol:	Errors Only
Default Repository Server:	SMB
Default Repository Document Path:	10.61.23.93:445
Default Repository Login Credentials:	/
Alt1 Repository Protocol:	Device
Alt1 Repository Server:	SMB
Alt1 Repository Document Path:	0.0.0.0:0
Alt1 Repository Login Credentials:	
Workflow Pool Protocol:	Device
Workflow Pool Server:	SMB
Workflow Pool Path:	0.0.0.0:0

## Email:

Default From Address:	Enabled
Confirmation Sheet:	syed.habibunnisa@xeroxqa.com
Auto Send to Self:	On
E-mail Security:	Disabled

## Scan to Mailbox:

View Mailboxes by Default:	Enabled
Storage Capacity (MB):	672 MB
Storage Used (MB):	80 MB
Cleanup of Public Folders:	Enabled
Cleanup of Created Folders:	Enabled
Cleanup Time:	Daily

## Scan to Home:

Friendly Name:	Disabled
Workflow Name:	Disabled
Auto Create Subdir:	Disabled
Append User Name to Path:	Disabled
Auto Create User Name Dir:	Disabled

## Scan To:

Cloud Services:	Enabled
Print From:	Disabled
Saved Jobs for Reprint:	Enabled
Print From USB:	Enabled
Print From MailBox:	Disabled
Cloud Services:	Disabled

**Accounting**

Accounting Mode: None  
Network Accounting: Disabled

**Security****Authentication Configuration**

Machine UI Authentication: Locally on the Device  
Home: Unlocked  
Jobs: Unlocked  
Device: Unlocked  
Device Website Authentication: Locally on the Device  
Authorization: Locally on the Device  
Retrieve E-mail from LDAP: Enabled

**Authentication Server:**

Kerberos Primary Realm: Kerberos  
Kerberos Primary Address: 0.0.0.0:88  
Kerberos Alt 1 Realm: 0.0.0.0:88  
Kerberos Alt 1 Address: 0.0.0.0:88  
SMB NT Domain:  
SMB Alt 1 NT Domain:  
Smartcard Ctrl Server: 0.0.0.0:443  
Smartcard Ctrl Domain:  
SmartCard OCSP URL:  
Card Reader Upgrade Policy: Enabled  
Card Reader Firmware Version:

**Xerox Secure Access:**

Secure Access Server: Disabled  
Secure Access Path: 0.0.0.0:443

**Audit Log:**

IP Sec: Enabled  
IP Filtering: Disabled  
IP Filtering: Disabled

**Security Certificates**

Machine Certificate: Signed  
Root Certificates Installed: 54  
802.1x: Disabled

**Job Data Removal:**

Scheduled: Disabled  
Scheduled Frequency: Monthly

**FIPS 140-3:**

TLS: Disabled  
TLS Hash: TLS 1.2 and TLS 1.3  
SHA-1, SHA-256 and above  
Trellix Embedded Control: Enhanced Security

**Extensible Service Setup**

Third Generation Browser: X3G\_3.24.23\_2.40.5\_012\_01.00.00  
Widget Version: v1.3.17 c8 20140613  
Widget Version: v2.5.04 g9 20240123

