

37601

Xerox® VersaLink® C620 Color Printer

Configuration Report

Printed at Mar 07, 2025 18:23



Common User Data

Machine Name: Xerox VersaLink C620 (6C:CB:6A)
 IP Address: 10.61.16.30
 Machine Serial Number: UMQ000558
 Machine URL: https://10.61.16.30
 Machine Activation Date: Jul 09, 2024 21:15:45
 Black Impressions: 2141
 Color Impressions: 3166
 Total Impressions: 5307

Machine Profile

Xerox Asset Tag:
 Customer Asset Tag:
 Service Phone Number:
 Customer Support Number:
 Supplies Phone Number:
 System Administrator: Not set
 Machine Location: machine location not set

Managed By

Primary MB Server:

Machine Hardware

Foreign Interface Card: not present
 Device RAM Size: 1984 MB
 Device Storage Size: used=2991MB/total=14004MB (eMMC)
 EPC Memory Size: 187 MB
 Productivity Kit: Not Installed
 Finisher Type: Simple Catch Tray
 Finisher Punch: None
 Finisher Folder: not present

General Setup

Remote Services: Enabled
 Remote Software Download: Enabled
 Remote Services Trans. Time: 06:44
 Xerox Workplace Cloud: Enabled
 E-mail Alerts: Disabled
 Service Plan: Plan Activated
 Geographic Region: unknown
 JMT Offset: +05:30
 Cloning Installation: Allowed (Encrypted Files Only)
 File Sharing: Enabled
 BIG2: Lossless

Energy Saver

Deep Sleep: Enabled
 Energy Saver Mode: Job Activated

Smart Proximity Sensor

Wake on Arrival: Not Available
 Sleep on Departure:

Software Versions

Device Software: 122.026.005.05800
 Patch Version: None
 Network Controller: 122.026.05800
 JI Panel Firmware: 6.2
 Marking Engine: 230.322
 Finisher: 000.000.000
 Machine Upgrades: Allowed
 Last Successful Upgrade: March 6, 2025 16:46:25

Media Trays

Tray 1: Plain, White and A4 (210 x 297 mm)
 Tray 2: Plain, White and A4 (210 x 297 mm)
 Tray 3: Plain, White and A4 (210 x 297 mm)
 Tray 4: Plain, White and A4 (210 x 297 mm)
 Tray 5: Plain, White and A4 (210 x 297 mm)
 Bypass Tray: Plain, White and Letter (8.5 x 11")

Installed Options

Options: Installed

Connectivity

Mobile Workflows

AirPrint Printing: Enabled
 Mopria Printing: Enabled

Physical Connections

USB Settings

USB Type A Ports: All Enabled
 USB Type B Port: Enabled

Wired:

Ethernet MAC Address: 12:57:d3:6c:cb:6a
 Ethernet Speed/Duplex Setting: auto
 Disabled

Wireless:

Wireless MAC Address:
 Network Name (SSID):
 BSSID:
 Security Mode:
 Encryption Algorithm:
 Status:
 Wi-Fi Direct: Enabled
 Wireless Hardware: Not Installed

Wi-Fi Protected Setup™ (WPS) Name:

Access Point (SSID):

Show Password on Device Touch Screen:

NFC:

iBeacon (Bluetooth®) for AirPrint DL...: Enabled
 iBeacon Hardware: Enabled
 Bluetooth Device Address: Not Installed
 iBeacon IP Address:

Protocols

TCP/IPv4:

IP Address: Enabled 10.61.16.30
 Subnet Mask: 255.255.255.0
 Router/Gateway: 10.61.16.1
 Automatic Addressing: DHCP
 DHCP Server: 10.61.13.223
 DHCP Lease Expiration: Fri Mar 14 10:17:27 2025
 BOOTP Broadcast: Disabled
 Self Assigned Address State: Enabled
 Self Assigned Address:

TCP/IPv6:

Link Local Address: Enabled fe80::1057:d3ff:fe6c:cb6a
 Use Router Supplied Prefix: Enabled
 Stateless Global Address 1: fd00:0:2:116:1057:d3ff:fe6c:cb6a
 Stateless Global Address 2: ::
 Manual Address:
 DHCP Addressing: Use DHCP as directed by a router
 DHCP Address:
 Default Gateway: fe80::8afc:5dff:fe75:e282
 DUID (DHCP Unique Identifier):

DNS Settings:

Requested Host Name: XRX1257D36CCB6A
 Verified Host Name:
 Requested Domain Name:
 Verified Domain Name:
 Multicast DNS: Enabled
 Release DHCP Leases and DNS Registrati...: Disabled
 Primary DNS Server: 10.61.7.15
 Prefer IPv6 DNS over IPv4: Enabled

Bonjour:

Bonjour Printer Name: Xerox VersaLink C620 (6C:CB:6A)

HTTP:

Force Traffic over Secure Connection (H...: Enabled
 IPP: Enabled

SNMP

SNMP v1/v2: Enabled
 SNMP v3: Disabled

LPR/LPD:

Raw IP Printing: Enabled

LDAP

LDAP Server 1 Primary LDAP Address: 0.0.0.0:389
 LDAP Server 1 Search Directory Root:
 LDAP Server 1 Secure Connection (LDA...: Disabled
 LDAP Server 1 Validate Server Certificate...: Disabled

SMTP

SMTP Server: 0.0.0.0:25
 Connect Encryption (TLS): No Encryption
 Validate Server Certificate (TLS):

Protocols (cont.)

POP3
 POP3 Server: 0.0.0.0:110
 POP3 Secure Connection (TLS): Disabled
 POP3 Validate Server Certificate:
 E-mail Address:
SMTP: Disabled
FTP Client: Enabled
 FTP Client Mode: Passive
Web Services on Device: Enabled

Fonts

Printing
 Banner Sheet: Disabled
 Error Sheets: Enabled
 Paper Substitution: Enabled
 Tray Priority: 1,2,3,4,5,6
 Archival Marking Mode: Off
PostScript
 Level: 3
 Version: 3021.101
PCL
 Version: 6
 Font Name: Courier
Custom Color Tables
 Label: Not Installed
Print From: Enabled
 Saved Jobs for Reprint: Enabled
 Print From USB: Enabled
 Cloud Services: Disabled

Accounting

Accounting Mode: None
 Network Accounting: Disabled

Security

Authentication Configuration

Machine UI Authentication: Locally on the Device
 Home: Unlocked
 Jobs Pathway: Unlocked
 Printer Pathway: Unlocked
Device Website Authentication: Locally on the Device
 Authorization: Locally on the Device

Authentication Server:

Kerberos
Xerox Secure Access: Disabled
Audit Log: Enabled
IPsec: Disabled
IP Filtering: Disabled

Security Certificates

Machine Certificate: Signed
 Root Certificates Installed: 54
SSL/TLS: Disabled

Job Data Removal:

Scheduled: Disabled
IPS 140-3: Disabled

TLS: TLS 1.2 and TLS 1.3
 TLS Hash: SHA-1, SHA-256 and above
Trellix Embedded Control: Enhanced Security