

Common User Data

Machine Name: Xerox VersaLink C415 Color MFP (46:2...
IP Address: 10.61.12.154
Machine Serial Number: YCQ293082
Fax Line 1:
Machine URL: https://10.61.12.154
Machine Activation Date: Jul 18, 2024 17:05:04
Black Impressions: 1334
Color Impressions: 4218
Total Impressions: 5552

Machine Profile

Xerox Asset Tag:
Customer Asset Tag:
Service Phone Number:
Customer Support Number:
Supplies Phone Number:
System Administrator:
Machine Location:
Managed By
Primary MB Server:

System Administrator name not set
machine location not set

Machine Hardware

Fax Card: Embedded; 1 Line
Fax Memory Size: 0 MB
Foreign Interface Card: not present
Device RAM Size: 1984 MB
Device Storage Size: used=3074MB/total=14004MB (eMMC)
EPC Memory Size: 187 MB
Productivity Kit: Not Installed
Finisher Type: Simple Catch Tray
Finisher Punch: None
Finisher Folder: not present
Multi-feed Detection Kit: Not Installed

General Setup

Remote Services: Enabled
Remote Software Download: Enabled
Remote Services Trans. Time: 13:34
Xerox Workplace Cloud: Enabled
E-mail Alerts: Disabled
Service Plan: Disabled
Geographic Region: unknown
GMT Offset: +05:30
Cloning Installation: Allowed (Encrypted Files Only)
File Sharing: Enabled
JBIG2: Lossless

Energy Saver

Deep Sleep: Enabled
Energy Saver Mode: Job Activated

Smart Proximity Sensor

Wake on Arrival: Not Available
Sleep on Departure:

Software Versions

Device Software: 122.028.005.05000
Patch Version: None
Network Controller: 122.028.05000
UI Panel Firmware: 6.2
Marking Engine: 230.320
Document Feeder: 230.320
Finisher: 000.000.000
Fax: 003.021.016
Scanner: 230.320
Machine Upgrades:
Last Successful Upgrade: February 24, 2025 16:12:11

Media Trays

Tray 1: Plain, White and A4 (210 x 297 mm)
Manual Feeder: Plain, White and A4 (210 x 297 mm)

Installed Options

PS: Installed

Connectivity

Mobile Workflows

AirPrint Printing: Enabled
Mopria Printing: Enabled
AirPrint / Mopria Scanning: Enabled
Authentication Required: Disabled

Physical Connections

USB Settings
USB Type A Ports: All Disabled
USB Type B Port: Disabled
Wired:
Ethernet MAC Address: Enabled
Ethernet Speed/Duplex Setting: 78:8c:77:46:20:25
auto

Disabled

Wireless:

Wireless MAC Address:

Network Name (SSID):

BSSID:

Security Mode:

Encryption Algorithm:

Status: Enabled

Wi-Fi Direct: Not Installed

Wireless Hardware:

Wi-Fi Protected Setup (WPS) Name:

Access Point (SSID):

Show Password on Device Touch Screen:

NFC: Enabled

iBeacon (Bluetooth®) for AirPrint Di... Enabled

iBeacon Hardware: Not Installed

Bluetooth Device Address:

iBeacon IP Address:

Protocols

TCP/IPV4:

IP Address: 10.61.12.154
Subnet Mask: 255.255.255.0
Router/Gateway: 10.61.12.1
Automatic Addressing: DHCP
DHCP Server: 10.61.13.224
DHCP Lease Expiration: Mon Mar 3 16:22:13 2025
BOOTP Broadcast: Disabled
Self Assigned Address State: Enabled
Self Assigned Address:

TCP/IPV6:

Link Local Address: Enabled
fe80::7a8c:77ff:fe46:2025
Use Router Supplied Prefix: Enabled
Stateless Global Address 1: Enabled
Stateless Global Address 2: fd00:0:2:112:7a8c:77ff:fe46:2025
Manual Address: ::
DHCP Addressing: Use DHCP as directed by a router
DHCP Address: fe80::8afc:5dff:fe75:e282
Default Gateway: fe80::8afc:5dff:fe75:e282
DUID (DHCP Unique Identifier):

DNS Settings:

Requested Host Name: XRX788C77462025
Verified Host Name:
Requested Domain Name:
Verified Domain Name:
Multicast DNS: Enabled
Release DHCP Leases and DNS Registrati... Disabled
Primary DNS Server: 10.61.7.15
Prefer IPv6 DNS over IPv4: Enabled

Bonjour:

Bonjour Printer Name: Xerox VersaLink C415 Color MFP (46:2...

HTTP:

Force Traffic over Secure Connection (H... Enabled
IPP: Yes
Enabled

SNMP

SNMP v1/v2: Enabled
SNMP v3: Disabled

LPR/LPD:

Enabled

Raw IP Printing:

Enabled

LDAP

LDAP Server 1 Primary LDAP Address: 0.0.0.389
LDAP Server 1 Search Directory Root:
LDAP Server 1 Secure Connection (LDA... Disabled
LDAP Server 1 Validate Server Certificate... Disabled

SMTP

SMTP Server: 0.0.0.25
Connect Encryption (TLS): No Encryption
Validate Server Certificate (TLS):
SMTP Authentication Type: Basic Auth with SMTP

Protocols (cont.)

POP3	
POP3 Server:	0.0.0.0:110
POP3 Secure Connection (TLS):	Disabled
E-mail Address:	
NTP:	Disabled
FTP Client:	Enabled
FTP Client Mode:	Passive
Web Services on Device:	Enabled

Apps**Printing**

Banner Sheet:	Enabled
Error Sheets:	Enabled
Paper Substitution:	Enabled
Tray Priority:	1,5
Archival Marking Mode	Off
PostScript	Installed
Level:	3
Version:	3021.101
PCL	
Version:	6
Font Name:	Courier
Custom Color Tables	Enabled
Label:	Not Installed
Fax:	Disabled

Fax Line1:	
Fax Line2:	
Server Fax:	Enabled
Repository Protocol:	SMB
Repository Server:	0.0.0.0:0
Repository Document Path:	

Workflow Scanning:

Enabled

Email:

Enabled

Enabled

672 MB

50 MB

Enabled

Enabled

Daily

Disabled

Enabled

Disabled

Enabled/Displayed

Disabled

Disabled

Disabled

Accounting

None

Disabled

Security**Authentication Configuration**

Machine UI Authentication:	Locally on the Device
Home:	Unlocked
Jobs:	Unlocked
Device:	Unlocked
Device Website Authentication:	Locally on the Device
Authorization:	Locally on the Device
Retrieve E-mail from LDAP:	Enabled

Authentication Server:

Kerberos

Disabled

Enabled

Disabled

Disabled

Signed

54

Disabled

Disabled

Disabled

TLS 1.2 and TLS 1.3

SHA-1, SHA-256 and above

Enhanced Security

Common User Data

Machine Name: Xerox VersaLink C415 Color MFP (46:2...
IP Address: 10.61.12.154
Machine Serial Number: YCQ293082
Fax Line1:
Machine URL: https://10.61.12.154
Machine Activation Date: Jul 18, 2024 17:05:04
Black Impressions: 1335
Color Impressions: 4219
Total Impressions: 5554

Machine Profile

Xerox Asset Tag:
Customer Asset Tag:
Service Phone Number:
Customer Support Number:
Supplies Phone Number:
System Administrator:
Machine Location:
Managed By
Primary MB Server:
System Administrator name not set
machine location not set

Machine Hardware

Fax Card: Embedded; 1 Line
Fax Memory Size: 0 MB
Foreign Interface Card: not present
Device RAM Size: 1984 MB
Device Storage Size: used=3074MB/total=14004MB (eMMC)
EPC Memory Size: 187 MB
Productivity Kit: Not Installed
Finisher Type: Simple Catch Tray
Finisher Punch: None
Finisher Folder: not present
Multi-feed Detection Kit: Not Installed

General Setup

Remote Services: Enabled
Remote Software Download: Enabled
Remote Services Trans. Time: 13:34
Xerox Workplace Cloud: Enabled
E-mail Alerts: Disabled
Service Plan: Plan Activated
Geographic Region: unknown
Startup Config Report: Enabled
GMT Offset: +05:30
Cloning Installation: Allowed (Encrypted Files Only)
Allow Print Submission of Clone Files: Enabled
File Sharing: Enabled
JBIG2: Lossless
Energy Saver
Deep Sleep: Enabled
Energy Saver Mode: Job Activated
Sleep Mode Timer: 120 minutes
Auto-Off: Disabled

Software Versions

Device Software: 122.028.005.05000
Patch Version: None
Network Controller: 122.028.05000
UI Panel Firmware: 6.2
User Interface: 122.028.05000
Marking Engine: 230.320
Copy Controller: 122.028.05000
Document Feeder: 230.320
Finisher: 000.000.000
Fax: 003.021.016
OS: 230.320
Scanner: 230.320
Software Upgrade: 005.010
ALTBOT Software Upgrade: 005.010
Machine Upgrades: Allowed
Last Successful Upgrade: February 24, 2025 16:12:11
Scheduled Auto Upgrades: Disabled
Auto Upgrade Start Time: Daily
Auto Upgrade Server: 0.0.0.0:21

Media Trays

Tray 1: Plain, White and A4 (210 x 297 mm)
Manual Feeder: Plain, White and A4 (210 x 297 mm)

Connectivity

Mobile Workflows

AirPrint Printing: Enabled
Mopria Printing: Enabled
AirPrint / Mopria Scanning: Enabled
Authentication Required: Disabled
Universal Print: Disabled
Universal Print Registration Status: Not Registered

Physical Connections

USB Settings
USB Type A Ports: All Disabled
USB Type B Port: Disabled
Connection Timeout: 5 seconds
Wired: Enabled
Ethernet MAC Address: 78:8c:77:46:20:25
Ethernet Speed/Duplex Setting: auto
Wireless: Disabled

Wireless MAC Address:
Network Name (SSID):
BSSID:
Security Mode:
Encryption Algorithm:
Status:

Wi-Fi Direct: Enabled
Wireless Hardware: Not Installed

Wi-Fi Protected Setup (WPS) Name:
Connection Method:
Subnet Prefix Address:
Access Point (SSID):
Show Password on Device Touch Screen:

NFC: Enabled
iBeacon (Bluetooth®) for AirPrint Di...: Enabled
iBeacon Hardware: Not Installed
Bluetooth Device Address:
iBeacon IP Address:

Protocols

TCP/IPv4:

IP Address: Enabled
10.61.12.154
Subnet Mask: 255.255.255.0
Router/Gateway: 10.61.12.1
Automatic Addressing: DHCP
DHCP Server: 10.61.13.224
DHCP Lease Expiration: Mon Mar 3 16:22:13 2025
BOOTP Broadcast: Disabled
Self Assigned Address State: Enabled
Self Assigned Address:

TCP/IPv6:

Link Local Address: Enabled
fe80::7a8c:77ff:fe46:2025
Use Router Supplied Prefix: Enabled
Stateless Global Address 1: fd00:0:2:112:7a8c:77ff:fe46:2025
Stateless Global Address 2: ::
Manual Address:
DHCP Addressing: Use DHCP as directed by a router
DHCP Address:
Default Gateway: fe80::8afc:5dff:fe75:e282
DUID (DHCP Unique Identifier):

DNS Settings:

Requested Host Name: XRX788C77462025
Verified Host Name:
Requested Domain Name:
Verified Domain Name:
Multicast DNS: Enabled
Release DHCP Leases and DNS Registrati...: Disabled
Primary DNS Server: 10.61.7.15
Alternate DNS Server 1: 10.61.10.6
Alternate DNS Server 2: ::
DNS Connection Timeout: 5
Append Device Domain: Enabled
Append Parent Domains: Disabled
DNS Domain Search List: XEROXQA.COM.
Prefer IPv6 DNS over IPv4: Enabled

Installed Options

PS: Installed

Protocols (cont.)

Bonjour:
 Bonjour Printer Name: Xerox VersaLink C415 Color MFP (46.2...
HTTP:
 Port Number: 80
 Force Traffic over Secure Connection (H...: Yes
 Secure HTTP Port Number: 443
 Proxy Server: Manual
 Proxy Server Address: 10.177.8.91:8080
 IPP: Enabled
 Secure IPP Mode: IPP and Secure IPPS
 IPP Network Path: http://10.61.12.154:631
SNMP
 SNMP v1/v2: Enabled
 SNMP v3: Disabled
LPR/LPD:
 Port Number: 515
 PDL Switching: Disabled
 PDL Banner Override: Disabled
Raw IP Printing:
 Port Number 1: 9100
 Bidirectional: Disabled
 End of Job Timeout: 300
 PDL Switching: Disabled
LDAP
 LDAP Server 1 Friendly Name:
 LDAP Server 1 Primary LDAP Address: 0.0.0.0:389
 LDAP Server 1 Alternate LDAP Address: 0.0.0.0:389
 LDAP Server 1 Search Directory Root:
 LDAP Server 1 Secure Connection (LDA...: Disabled
 LDAP Server 1 Validate Server Certificate...: Disabled
SMTP
 SMTP Server: 0.0.0.0:25
 Connect Encryption (TLS): No Encryption
 Validate Server Certificate (TLS): 10240
 Max Message Size (KB): 1
 Number of Fragments: 300000
 Total Job Size (KB): Page Boundary
 Job Splitting Boundary: None
 Credentials for Auto E-mails: None
 Credentials for Walkup User: None
 SMTP Authentication Type: Basic Auth with SMTP
POP3
 POP3 Server: 0.0.0.0:110
 POP3 Secure Connection (TLS): Disabled
 E-mail Address:
 Receipt of E-mail via POP3: Disabled
 Send Confirm on Request: Enabled
 Incoming E-mail cover sheet: Enabled
NTP:
 Primary Server: 0.0.0.0:123
 Alternate Server: 0.0.0.0:123
SLP:
FTP Client:
 FTP Client Mode: Passive
Web Services on Device:
 WS-Discovery: Enabled
 WS-Discovery Multicast: Enabled
 WS-Print: Enabled
 WS-Scan: Enabled
Web Services
 Copy Submission: Enabled
 Digital Certificate Management and Securi...: Enabled
 Extensible Service Registration: Enabled
 Job Limits: Enabled
 Job Management Extension: Enabled
 Device Configuration: Enabled
 Scan Submission: Enabled
 Scan Workflow Management: Enabled
 Session Data: Enabled
 User Interface Configuration: Enabled
 EIP Proxy Configuration: Enabled
 Xerox Secure Access: Disabled
 EIP SNMP Configuration: Enabled
 Print Submission: Enabled
 Scan Template Mgmt: Enabled
 Mass Storage Access: Enabled
 Card Reader Access: Enabled
 Authentication & Accounting Configur...: Enabled
 Export Audit Log: Enabled
 Trellix Embedded Control: Enabled

Apps

Printing

Banner Sheet: Enabled
 Sys/Start Job: Disabled
 Delete Held Jobs After: 3 Day(s) 0 Hour(s) 0 Minute(s)
 Error Sheets: Enabled
 Paper Substitution: Enabled
 Tray Priority: 1,5
 Default Copies: 1
 Default Job Type: Normal Print
 Default Paper Size: x=8.50 inches, y=11.00 inches
 Default Paper Color: White
 Default 2 Sided Printing: 2 Sided
 Default Output Tray: Center Tray
 Default Output Color: Color
 Default Collated Sets: Enabled
 Default Stapling: Not Available
 Offsetting Between Jobs: No Offset Between Jobs
 Archival Marking Mode: Off
PostScript
 Level: 3
 Version: 3021.101
 Image Quality: Enhanced
PCL
 Version: 6
 Pitch Size: 10.00
 Point Size: 12.00
 Font Name: Courier
 Lines Per Page: 60
Custom Color Tables
 Label: Enabled
 Not Installed
 Disabled
Fax:
 Fax Line1:
 Fax Line2:
Server Fax:
 Confirmation Sheet: Enabled
 Delay Start: Errors Only
 Repository Protocol: Disabled
 Repository Server: SMB
 Repository Document Path: 0.0.0.0:0
Workflow Scanning:
 Confirmation Sheet: Enabled
 Default Repository Protocol: Off
 Default Repository Server: SMB
 Default Repository Document Path: 0.0.0.0:0
 Default Repository Login Credentials: Device
 Alt1 Repository Protocol: SMB
 Alt1 Repository Server: 0.0.0.0:0
 Alt1 Repository Document Path: Device
 Alt1 Repository Login Credentials: SMB
 Workflow Pool Protocol: 0.0.0.0:0
 Workflow Pool Server:
 Workflow Pool Path:
Email:
 Default From Address: Enabled
 Confirmation Sheet: Errors Only
 Auto Send to Self: Disabled
 E-mail Security: Disabled
Scan to Mailbox:
 View Mailboxes by Default: Enabled
 Storage Capacity (MB): 672 MB
 Storage Used (MB): 50 MB
 Cleanup of Public Folders: Enabled
 Cleanup of Created Folders: Enabled
 Cleanup Time: Daily
Scan to Home:
 Friendly Name:
 Workflow Name:
 Auto Create Subdir: Disabled
 Append User Name to Path: Disabled
 Auto Create User Name Dir: Disabled
Scan To:
 Cloud Services: Enabled
Print From:
 Saved Jobs for Reprint: Enabled/Displayed
 Print From USB: Disabled
 Print From MailBox: Enabled
 Cloud Services: Disabled

Accounting

Accounting Mode: None
Network Accounting: Disabled

Security

Authentication Configuration

Machine UI Authentication: Locally on the Device
Home: Unlocked
Jobs: Unlocked
Device: Unlocked
Device Website Authentication: Locally on the Device
Authorization: Locally on the Device
Retrieve E-mail from LDAP: Enabled

Authentication Server:

Kerberos Primary Realm: Kerberos
Kerberos Primary Address: 0.0.0.88
Kerberos Alt 1 Realm: Kerberos
Kerberos Alt 1 Address: 0.0.0.88
SMB NT Domain: SMB NT Domain
SMB Alt 1 NT Domain: SMB Alt 1 NT Domain
Smartcard Ctrl Server: 0.0.0.443
Smartcard Ctrl Domain: SmartCard Ctrl Domain
SmartCard OCSP URL: SmartCard OCSP URL
Card Reader Upgrade Policy: Enabled
Card Reader Firmware Version: Card Reader Firmware Version

Xerox Secure Access:

Secure Access Server: Disabled
Secure Access Path: 0.0.0.443

Audit Log:

Enabled

IP Sec:

Disabled

IP Filtering:

Disabled

Security Certificates

Machine Certificate: Signed
Root Certificates Installed: 54
802.1x: Disabled

Job Data Removal:

Scheduled: Disabled
Scheduled Frequency: Monthly

FIPS 140-3:

Disabled

TLS:

TLS Hash: TLS 1.2 and TLS 1.3
SHA-1, SHA-256 and above

Trellix Embedded Control:

Enhanced Security

Extensible Service Setup

Third Generation Browser: X3G_3 24.23 2.40.5_012_01.00:00
Widget Version: v1.3.17 c8 20140613
Widget Version: v2.5.04 g9 20240123

