

Common User Data

Machine Name: Xerox VersaLink B625 MFP (AC:E7:D5)
 IP Address: 10.61.12.146
 Machine Serial Number: UPQ100521
 Fax Line1: 3337
 Machine URL: https://10.61.12.146
 Machine Activation Date: Jan 01, 1970 05:30:00
 Total Impressions: 218

Machine Profile

Xerox Asset Tag:
 Customer Asset Tag:
 Service Phone Number:
 Customer Support Number:
 Supplies Phone Number:
 System Administrator: System Administrator name not set
 Machine Location: machine location not set

Managed By

Primary MB Server:

Machine Hardware

Fax Card: Embedded; 1 Line
 Fax Memory Size: 738 MB
 Foreign Interface Card: not present
 Device RAM Size: 3904 MB
 Device Storage Size: used=2982MB/total=0MB (eMMC)
 EPC Memory Size: 187 MB
 Productivity Kit: Not Installed
 Finisher Type: Simple Catch Tray
 Finisher Punch: None
 Finisher Folder: not present
 Multi-feed Detection Kit: Not Installed

General Setup

Remote Services: Enabled
 Remote Software Download: Enabled
 Remote Services Trans. Time: 19:50
 Xerox Workplace Cloud: Enabled
 E-mail Alerts: Disabled
 Service Plan: Plan Activated
 Geographic Region: unknown
 GMT Offset: +05:30
 Cloning Installation: Allowed (Encrypted Files Only)
 File Sharing: Enabled
 JBIG2: Lossless

Energy Saver

Deep Sleep: Enabled
 Energy Saver Mode: Job Activated

Smart Proximity Sensor

Wake on Arrival: Not Available
 Sleep on Departure:

Software Versions

Device Software: 122.025.005.01730
 Patch Version: None
 Network Controller: 122.025.01730
 UI Panel Firmware: 6.1
 Marking Engine: 230.318
 Document Feeder: 230.318
 Finisher: 000.000.000
 Fax: 003.021.013
 Scanner: 230.318

Machine Upgrades:

Last Successful Upgrade: January 20, 2025 20:23:07

Media Trays

Tray 1: Plain, White and A4 (210 x 297 mm)
 Tray 2: Plain, White and A4 (210 x 297 mm)
 Bypass Tray: Plain, White and A4 (210 x 297 mm)

Installed Options

PS: Installed

Connectivity

Mobile Workflows

AirPrint Printing: Enabled
 Mopria Printing: Enabled
 AirPrint / Mopria Scanning: Enabled
 Authentication Required: Disabled

Physical Connections

USB Settings
 USB Type A Ports: All Enabled
 USB Type B Port: Disabled
Wired:
 Ethernet MAC Address: Enabled
 Ethernet Speed/Duplex Setting: 78:8c:77:acc:e7:d5 auto
Wireless:
 Wireless MAC Address: Disabled
 Network Name (SSID):
 BSSID:
 Security Mode:
 Encryption Algorithm:
 Status:
Wi-Fi Direct: Enabled
 Wireless Hardware: Not Installed
 Wi-Fi Protected Setup (WPS) Name:
 Access Point (SSID):
 Show Password on Device Touch Screen:
NFC: Enabled
iBeacon (Bluetooth®) for AirPrint Di... Enabled
 iBeacon Hardware: Not Installed
 Bluetooth Device Address:
 iBeacon IP Address:

Protocols

TCP/IPv4: Enabled
 IP Address: 10.61.12.146
 Subnet Mask: 255.255.255.0
 Router/Gateway: 10.61.12.1
 Automatic Addressing: DHCP
 DHCP Server: 10.61.13.224
 DHCP Lease Expiration: Mon Jan 27 20:32:00 2025
 BOOTP Broadcast: Disabled
 Self Assigned Address State: Enabled
 Self Assigned Address:

TCP/IPv6: Enabled
 Link Local Address: fe80::7a8c:77ff:feacc:e7d5
 Use Router Supplied Prefix: Enabled
 Stateless Global Address 1: fd00:0:2:112:7a8c:77ff:feacc:e7d5
 Stateless Global Address 2: ::
 Manual Address:
 DHCP Addressing: Use DHCP as directed by a router
 DHCP Address:
 Default Gateway: fe80::8afc:5dff:fe75:e282
 DUID (DHCP Unique Identifier):

DNS Settings:
 Requested Host Name: XR788C77ACE7D5
 Verified Host Name:
 Requested Domain Name:
 Verified Domain Name:
 Multicast DNS: Enabled
 Release DHCP Leases and DNS Registrati...: Disabled
 Primary DNS Server: 10.61.7.15
 Prefer IPv6 DNS over IPv4: Enabled

Bonjour:
 Bonjour Printer Name: Xerox VersaLink B625 MFP (AC:E7:D5)
HTTP: Enabled
 Force Traffic over Secure Connection (H...: Yes
 IPP: Enabled

SNMP
 SNMP v1/v2: Enabled
 SNMP v3: Disabled

LPR/LPD: Enabled
Raw IP Printing: Enabled

LDAP
 LDAP Server 1 Primary LDAP Address: 0.0.0.0:389
 LDAP Server 1 Search Directory Root:
 LDAP Server 1 Secure Connection (LDA...: Disabled
 LDAP Server 1 Validate Server Certificate...: Disabled

SMTP
 SMTP Server: 0.0.0.0:25
 Connect Encryption (TLS): No Encryption
 Validate Server Certificate (TLS):

Protocols (cont.)

POP3	
POP3 Server:	0.0.0.0:110
POP3 Secure Connection (TLS):	Disabled
E-mail Address:	
NTP:	Disabled
FTP Client:	Enabled
FTP Client Mode:	Passive
Web Services on Device:	Enabled

Apps

Printing

Banner Sheet:	Enabled
Error Sheets:	Enabled
Paper Substitution:	Enabled
Tray Priority:	1,2,5

Archival Marking Mode

PostScript	Installed
Level:	3
Version:	3021.101

PCL

Version:	6
Font Name:	Courier

Custom Color Tables

Label:	Not Installed
--------	---------------

Fax:

Fax Line1:	Enabled/Displayed
Fax Line2:	3337

Server Fax:

Repository Protocol:	Enabled
Repository Server:	SMB
Repository Server:	10.61.23.93:445
Repository Document Path:	/

Workflow Scanning:

Enabled	Enabled
---------	---------

Email:

Enabled	Enabled
---------	---------

Scan to Mailbox:

Enabled	Enabled
---------	---------

Storage Capacity (MB):	672 MB
------------------------	--------

Storage Used (MB):	66 MB
--------------------	-------

Cleanup of Public Folders:	Enabled
----------------------------	---------

Cleanup of Created Folders:	Enabled
-----------------------------	---------

Cleanup Time:	Daily
---------------	-------

Scan to Home:

Disabled	Disabled
----------	----------

Scan To:

Enabled	Enabled
---------	---------

Cloud Services:	Disabled
-----------------	----------

Print From:

Enabled	Enabled
---------	---------

Saved Jobs for Reprint:	Enabled
-------------------------	---------

Print From USB:	Enabled
-----------------	---------

Print From MailBox:	Disabled
---------------------	----------

Cloud Services:	Disabled
-----------------	----------

Accounting

Accounting Mode:	None
Network Accounting:	Disabled

Security

Authentication Configuration

Machine UI Authentication:	Locally on the Device
----------------------------	-----------------------

Home:	Unlocked
-------	----------

Jobs:	Unlocked
-------	----------

Device:	Unlocked
---------	----------

Device Website Authentication:	Locally on the Device
--------------------------------	-----------------------

Authorization:	Locally on the Device
----------------	-----------------------

Retrieve E-mail from LDAP:	Enabled
----------------------------	---------

Authentication Server:

Kerberos	Disabled
----------	----------

Xerox Secure Access:

Disabled	Enabled
----------	---------

Audit Log:

Disabled	Disabled
----------	----------

IP Sec:

Disabled	Disabled
----------	----------

IP Filtering:

Disabled	Disabled
----------	----------

Security Certificates

Machine Certificate:	Signed
----------------------	--------

Root Certificates Installed:	54
------------------------------	----

802.1x:

Disabled	Disabled
----------	----------

Job Data Removal:

Scheduled:	Full
------------	------

FIPS 140-3:

Disabled	Disabled
----------	----------

TLS:

TLS Hash:	TLS 1.2 and TLS 1.3
-----------	---------------------

TLS Hash:	SHA-1, SHA-256 and above
-----------	--------------------------

Trellix Embedded Control:

Enhanced Security	Enhanced Security
-------------------	-------------------

Common User Data

Machine Name: Xerox VersaLink B625 MFP (AC:E7:D5)
 IP Address: 10.61.12.146
 Machine Serial Number: UPQ100521
 Fax Line 1: 3337
 Machine URL: https://10.61.12.146
 Machine Activation Date: Jan 01, 1970 05:30:00
 Total Impressions: 218

Machine Profile

Xerox Asset Tag:
 Customer Asset Tag:
 Service Phone Number:
 Customer Support Number:
 Supplies Phone Number:
 System Administrator: System Administrator name not set
 Machine Location: machine location not set
Managed By
 Primary MB Server:

Machine Hardware

Fax Card: Embedded; 1 Line
 Fax Memory Size: 738 MB
 Foreign Interface Card: not present
 Device RAM Size: 3904 MB
 Device Storage Size: used=2982MB/total=14004MB (eMMC)
 EPC Memory Size: 187 MB
 Productivity Kit: Not Installed
 Finisher Type: Simple Catch Tray
 Finisher Punch: None
 Finisher Folder: not present
 Multi-feed Detection Kit: Not Installed

General Setup

Remote Services: Enabled
 Remote Software Download: Enabled
 Remote Services Trans. Time: 19:50
 Xerox Workplace Cloud: Enabled
 E-mail Alerts: Disabled
 Service Plan: Plan Activated
 Geographic Region: unknown
 Startup Config Report: Enabled
 GMT Offset: +05:30
 Cloning Installation: Allowed (Encrypted Files Only)
 Allow Print Submission of Clone Files: Enabled
 File Sharing: Enabled
 JBIG2: Lossless
Energy Saver
 Deep Sleep: Enabled
 Energy Saver Mode: Job Activated
 Sleep Mode Timer: 120 minutes
 Auto-Off: Disabled

Software Versions

Device Software: 122.025.005.01730
 Patch Version: None
 Network Controller: 122.025.01730
 UI Panel Firmware: 6.1
 User Interface: 122.025.01730
 Marking Engine: 230.318
 Copy Controller: 122.025.01730
 Document Feeder: 230.318
 Finisher: 000.000.000
 Fax: 003.021.013
 OS: 230.318
 Scanner: 230.318
 Software Upgrade: 005.008
 ALTB00T Software Upgrade: 005.008
 Tray 2: A16.47_B2.3

Machine Upgrades:

Last Successful Upgrade: January 20, 2025 20:23:07
 Scheduled Auto Upgrades: Disabled
 Auto Upgrade Start Time: Daily
 Auto Upgrade Server: 0.0.0.21

Media Trays

Tray 1: Plain, White and A4 (210 x 297 mm)
 Tray 2: Plain, White and A4 (210 x 297 mm)
 Bypass Tray: Plain, White and A4 (210 x 297 mm)

Connectivity

Mobile Workflows

AirPrint Printing: Enabled
 Mopria Printing: Enabled
 AirPrint / Mopria Scanning: Enabled
 Authentication Required: Disabled
 Universal Print: Disabled
 Universal Print Registration Status: Not Registered

Physical Connections

USB Settings

USB Type A Ports: All Enabled
 USB Type B Port: Disabled
 Connection Timeout: 5 seconds

Wired:

Ethernet MAC Address: Enabled
 Ethernet Speed/Duplex Setting: 78.8c:77:ac:e7:d5 auto

Wireless:

Wireless MAC Address: Disabled

Network Name (SSID):

BSSID:

Security Mode:

Encryption Algorithm:

Status:

Wi-Fi Direct:

Wi-Fi Direct: Enabled
 Wireless Hardware: Not Installed

Wi-Fi Protected Setup (WPS) Name:

Connection Method:

Subnet Prefix Address:

Access Point (SSID):

Show Password on Device Touch Screen:

NFC:

NFC: Enabled

iBeacon (Bluetooth®) for AirPrint Di...

iBeacon Hardware: Not Installed

Bluetooth Device Address:

iBeacon IP Address:

Protocols

TCP/IPV4:

TCP/IPV4: Enabled
 IP Address: 10.61.12.146
 Subnet Mask: 255.255.255.0
 Router/Gateway: 10.61.12.1
 Automatic Addressing: DHCP
 DHCP Server: 10.61.13.224
 DHCP Lease Expiration: Mon Jan 27 20:32:00 2025
 BOOTP Broadcast: Disabled
 Self Assigned Address State: Enabled
 Self Assigned Address:

TCP/IPV6:

TCP/IPV6: Enabled
 Link Local Address: fe80::7a8c:77ff:feac:e7d5
 Use Router Supplied Prefix: Enabled
 Stateless Global Address 1: fd00:0:2:112:7a8c:77ff:feac:e7d5
 Stateless Global Address 2: ::
 Manual Address:
 DHCP Addressing: Use DHCP as directed by a router
 DHCP Address:
 Default Gateway: fe80::8afc:5dff:fe75:e282
 DUID (DHCP Unique Identifier):

DNS Settings:

DNS Settings:
 Requested Host Name: XRX788C77ACE7D5
 Verified Host Name:
 Requested Domain Name:
 Verified Domain Name:
 Multicast DNS: Enabled
 Release DHCP Leases and DNS Registrati...: Disabled
 Primary DNS Server: 10.61.7.15
 Alternate DNS Server 1: 10.61.10.6
 Alternate DNS Server 2: ::
 DNS Connection Timeout: 5
 Append Device Domain: Enabled
 Append Parent Domains: Disabled
 DNS Domain Search List: XEROXQA.COM
 Prefer IPv6 DNS over IPv4: Enabled

Installed Options

PS: Installed

Protocols (cont.)

Bonjour:	
Bonjour Printer Name:	Xerox VersaLink B625 MFP (AC:E7:D5)
HTTP:	
Port Number:	80
Force Traffic over Secure Connection (H...):	Yes
Secure HTTP Port Number:	443
Proxy Server:	Manual
Proxy Server Address:	10.177.8.91:8080
IPP:	Enabled
Secure IPP Mode:	IPP and Secure IPPS
IPP Network Path:	http://10.61.12.146:631
SNMP	
SNMP v1/v2:	Enabled
SNMP v3:	Disabled
LPR/LPD:	
Port Number:	515
PDL Switching:	Disabled
PDL Banner Override:	Disabled
Raw IP Printing:	
Port Number 1:	9100
Bidirectional:	Disabled
End of Job Timeout:	300
PDL Switching:	Disabled
LDAP	
LDAP Server 1 Friendly Name:	
LDAP Server 1 Primary LDAP Address:	0.0.0.0:389
LDAP Server 1 Alternate LDAP Address:	0.0.0.0:389
LDAP Server 1 Search Directory Root:	
LDAP Server 1 Secure Connection (LDA...):	Disabled
LDAP Server 1 Validate Server Certificate...:	Disabled
SMTP	
SMTP Server:	0.0.0.0:25
Connect Encryption (TLS):	No Encryption
Validate Server Certificate (TLS):	
Max Message Size (KB):	10240
Number of Fragments:	1
Total Job Size (KB):	300000
Job Splitting Boundary:	Page Boundary
Credentials for Auto E-mails:	None
Credentials for Walkup User:	None
POP3	
POP3 Server:	0.0.0.0:110
POP3 Secure Connection (TLS):	Disabled
E-mail Address:	
Receipt of E-mail via POP3:	Disabled
Send Confirm on Request:	Enabled
Incoming E-mail cover sheet:	Enabled
NTP:	
Primary Server:	0.0.0.0:123
Alternate Server:	0.0.0.0:123
SLP:	
SLP:	Disabled
FTP Client:	
FTP Client Mode:	Passive
Web Services on Device:	
WS-Discovery:	Enabled
WS-Discovery Multicast:	Enabled
WS-Print:	Enabled
WS-Scan:	Enabled
Web Services	
Copy Submission:	Enabled
Digital Certificate Management and Securi...:	Enabled
Extensible Service Registration:	Enabled
Job Limits:	Enabled
Job Management Extension:	Enabled
Device Configuration:	Enabled
Scan Submission:	Enabled
Scan Workflow Management:	Enabled
Session Data:	Enabled
User Interface Configuration:	Enabled
EIP Proxy Configuration:	Enabled
Xerox Secure Access:	Disabled
EIP SNMP Configuration:	Enabled
Print Submission:	Enabled
Scan Template Mgmt:	Enabled
Mass Storage Access:	Enabled
Card Reader Access:	Enabled
Authentication & Accounting Configur...:	Enabled
Export Audit Log:	Enabled
Trellix Embedded Control:	Enabled

Apps

Printing

Banner Sheet:	Enabled
Sys/Start Job:	Disabled
Delete Held Jobs After:	3 Day(s) 0 Hour(s) 0 Minute(s)
Error Sheets:	Enabled
Paper Substitution:	Enabled
Tray Priority:	1, 2, 5
Default Copies:	1
Default Job Type:	Normal Print
Default Paper Size:	x=8.50 inches, y=11.00 inches
Default Paper Color:	White
Default 2 Sided Printing:	2 Sided
Default Output Tray:	Center Tray
Default Output Color:	Black & White
Default Collated Sets:	Enabled
Default Stapling:	Not Available
Offsetting Between Jobs:	No Offset Between Jobs
Archival Marking Mode	
PostScript:	Installed
Level:	3
Version:	3021.101
Image Quality:	Enhanced

PCL

Version:	6
Pitch Size:	10.00
Point Size:	12.00
Font Name:	Courier
Lines Per Page:	60

Custom Color Tables

Label:	Enabled
	Not Installed

Fax:

Fax Line1:	Enabled/Displayed
Fax Line2:	3337

Server Fax:

Confirmation Sheet:	Enabled
Delay Start:	On
Repository Protocol:	Disabled
Repository Server:	SMB
Repository Document Path:	10.61.23.93:445

Workflow Scanning:

Confirmation Sheet:	Enabled
Default Repository Protocol:	Errors Only
Default Repository Server:	SMB
Default Repository Document Path:	0.0.0.0:0
Default Repository Login Credentials:	Device
Alt1 Repository Protocol:	SMB
Alt1 Repository Server:	0.0.0.0:0
Alt1 Repository Document Path:	
Alt1 Repository Login Credentials:	Device
Workflow Pool Protocol:	SMB
Workflow Pool Server:	0.0.0.0:0
Workflow Pool Path:	

Email:

Default From Address:	Enabled
Confirmation Sheet:	
Auto Send to Self:	Errors Only
E-mail Security:	Disabled

Scan to Mailbox:

View Mailboxes by Default:	Enabled
Storage Capacity (MB):	Enabled
Storage Used (MB):	672 MB
Cleanup of Public Folders:	66 MB
Cleanup of Created Folders:	Enabled
Cleanup Time:	Enabled
	Daily
	Disabled

Scan to Home:

Friendly Name:	
Workflow Name:	
Auto Create Subdir:	Disabled
Append User Name to Path:	Disabled
Auto Create User Name Dir:	Disabled

Scan To:

Cloud Services:	Enabled
	Disabled

Print From:

Saved Jobs for Reprint:	Enabled
Print From USB:	Enabled
Print From MailBox:	Disabled
Cloud Services:	Disabled

Accounting

Accounting Mode: None
 Network Accounting: Disabled

Security

Authentication Configuration

Machine UI Authentication: Locally on the Device
 Home: Unlocked
 Jobs: Unlocked
 Device: Unlocked
 Device Website Authentication: Locally on the Device
 Authorization: Locally on the Device
 Retrieve E-mail from LDAP: Enabled

Authentication Server:

Kerberos Primary Address: Kerberos
 Kerberos Primary Realm: 0.0.0.0:88
 Kerberos Alt 1 Realm: 0.0.0.0:88
 Kerberos Alt 1 Address: 0.0.0.0:88
 SMB NT Domain:
 SMB Alt 1 NT Domain:
 Smartcard Ctrl Server: 0.0.0.0:443
 Smartcard Ctrl Domain:
 SmartCard OCSF URL:
 Card Reader Upgrade Policy: Enabled
 Card Reader Firmware Version:

Xerox Secure Access:

Secure Access Server: Disabled
 Secure Access Server: 0.0.0.0:443
 Secure Access Path:

Audit Log:

Enabled

IP Sec:

Disabled

IP Filtering:

Disabled

Security Certificates

Machine Certificate: Signed
 Root Certificates Installed: 54

802.1x:

Disabled

Job Data Removal:

Scheduled: Full
 Scheduled Frequency: Daily

FIPS 140-3:

Disabled

TLS:

TLS Hash: TLS 1.2 and TLS 1.3
 SHA-1, SHA-256 and above

Trellix Embedded Control:

Enhanced Security

Extensible Service Setup

Third Generation Browser: X3G_3.24.23_2.40.5_012_01.00.00
 Widget Version: v1.3.17 c8 20140613
 Widget Version: v2.5.04 g9 20240123