

Protocols (cont.)

POP3	
POP3 Server:	0.0.0.0:110
POP3 Secure Connection (TLS):	Disabled
POP3 Validate Server Certificate:	
E-mail Address:	
NTP:	
	Enabled
FTP Client:	
	Enabled
FTP Client Mode:	Passive
Web Services on Device	Enabled

Apps

Printing

Banner Sheet:	Disabled
Error Sheets:	Enabled
Paper Substitution:	Enabled
Tray Priority:	1,2,3,4,5
PostScript	Installed
Level:	3
Version:	3021.101
PCL	

PCL

Font Name:	Course:
Custom Color Tables	Enabled
Label:	Not Installed

Fax:

Repository Protocol:	Enabled
Repository Server:	SMB
Repository Document Path:	10.61.23.0: /

Workflow Scanning:

Scan to Mailbox:	Disabled
Storage Capacity (MB):	45924 MB
Storage Used (MB):	2417 MB
Cleanup of Public Folders:	Enabled
Cleanup of Created Folders:	Enabled
Cleanup Time:	Daily

Scan to Home

Cloud Services	Doubled
-----------------------	----------------

Print From:

Saved Jobs for Reprint:	Enabled
Print From USB:	Enabled

Accounting

Accounting Mode:	None
Network Accounting:	Disabled

Conclusions

Authentication Configuration

Authentication Configuration	
Machine UI Authentication:	Locally on the Device
Home	Unlocked
Jobs:	Unlocked
Device	Unlocked
Device Website Authentication:	Locally on the Device

Retrieve E-mail from LDAP:	Enabled
Authentication Server:	None (local)

Audit Log.

IP Sec.	Disabled
IP Filtering.	Disabled

Security Cer

Midnight Certificate	539104
Root Certificates Installed	55
802.1x	55

Job Data Removal.

Scheduled:	Disabled
FIPS 140-3:	Disabled

<p>TLS.</p> <p>TLS Hash:</p> <p>Intelix Embedded Control.</p>	<p>TLS-1, TLS-1.1 and TLS-1.2</p> <p>SHA-1, SHA-256 and above</p> <p>Confidential security</p>
---	--

Common User Data

Machine Name: Xerox AltaLink C8270 Color MFP (A2:2...
IPv4 Address: 10.61.16.12
Machine Serial Number: ZQZ654008
Fax Line1:
Machine URL: https://10.61.16.12
Machine Activation Date: Jun 19, 2025 16:13:27
Black Impressions: 82126
Color Impressions: 116584
Total Impressions: 198710

Machine Profile

Xerox Asset Tag:
Customer Asset Tag:
Service Phone Number:
Customer Support Number:
Supplies Phone Number:
System Administrator:
Machine Location:
Managed By: Not set
machine location not set

Machine Hardware

Fax Card: Not Present
Fax Memory Size: 0 MB
Device RAM Size: 8192 MB
Device Storage Size: used: 3218MB/total: 256060MB (SSD)
EPC Memory Size: 1000 MB
Finisher Type: Offsetting Catch Tray
Finisher Punch: None
Finisher Folder: not present

General Setup

Remote Services: Enabled
Remote Software Download: Enabled
Remote Services Trans. Time: 14:33
Xerox Workplace Cloud: Disabled
E-mail Alerts: Disabled
Billing Impression Mode: A4 Impressions
Geographic Region: unknown
GMT Offset: +05:30
Cloning Installation: Allowed (Encrypted Files Only)

Energy Saver

Deep Sleep: Enabled
Energy Saver Mode: Job Activated

Smart Proximity Sensor

Wake on Arrival: Enabled
Close on Departure: Disabled

Software Versions

Device Software: 122.040.005.15400
Patch Version: None
Network Controller: 122.040.15400
UI Panel Firmware: 003.005.000.01
Marking Engine: 014.045.000
Document Feeder: 001.033.000
Fax: 004.000.000
Fax: 004.000.000

Machine Upgrades:

Last Successful Upgrade: Allowed
June 20, 2025 10:55 AM

Media Trays

Tray 1: Plain, White and A4 (210 x 297 mm)
Tray 2: Plain, White and A4 (210 x 297 mm)
Tray 3: Plain, White and A4 (210 x 297 mm)
Tray 4: Plain, White and A4 (210 x 297 mm)
Bypass Tray: Envelope, White and No. 9 Envelope(98 x 2...

Installed Options

PS: Installed

Connectivity

Mobile Workflows

AirPrint Printing: Enabled
Mopria Printing: Enabled
AirPrint / Mopria Scanning: Enabled
Authentication Required: Disabled

Physical Connections

USB Settings: All Enabled
USB Type A Ports: Enabled
USB Type B Port: Enabled
Wired: 9c93:4e:a2:29:af
Ethernet MAC Address: auto
Ethernet Speed/Duplex Setting: Disabled

Wireless:

Wireless MAC Address:
Network Name (SSID):
BSSID:
Security Mode:
Encryption Algorithm:
Status: Disabled
Not Installed

Wireless Hardware:
Wi-Fi Protected Setup™ (WPS) Name:
Access Point (SSID):
Show Password on Device Touch Screen:

NFC: Enabled
iBeacon (Bluetooth®) for AirPrint Di...: Enabled
iBeacon Hardware: Not Installed
Bluetooth Device Address:
iBeacon IP Address:

Protocols

IPv4 Address: 10.61.16.12
Subnet Mask: 255.255.255.0
Router/Gateway: 10.61.16.1
Automatic Addressing: DHCP
DHCP Server: 10.61.13.223
DHCP Lease Expiration: Fri Jun 27 10:41:04 2025
BOOTP Broadcast: Disabled
Kerberos Authentication Type: Disabled

TCP/IPV6:

Link Local Address: Enabled
Use Router Supplied Prefix: Enabled

Static IP Address: 10.61.16.12
Manual Address:
DHCP Addressing: Use DHCP as directed by a router
DHCP Address: fd00:0:2:116:7229:7ba3:b172:192c
DHCP Gateway: fe80::8afc:5aff:fe75:e282
DHCP/DHCP-Unique Identifier: 000100017fe7a9e48c934ee229af

DNS Settings:

Requested Host Name: 10.61.16.12
Verified Host Name:
Requested Domain Name:
Verified Domain Name:
Multicast DNS: Enabled
Release DHCP Lease and DNS Registration: Disabled
Primary DNS Server: 10.61.7.16

Bonjour:

Bonjour Printer Name: Xerox AltaLink C8270 Color MFP (A2:2...
Bonjour Printer Name: Xerox AltaLink C8270 Color MFP (A2:2...
Bonjour Printer Name: Xerox AltaLink C8270 Color MFP (A2:2...

SNMP:

SNMP v1/v2: Enabled
SNMP v3: Enabled
SNMP v3 Security: Disabled

LPR/LPD:
Raw IP Printing:
LDAP

LDAP Server 1 Primary LDAP Address: 0.0.0.0:389
LDAP Server 1 Search Directory Root:

LDAP Server 1 Validate Server Certificate: Disabled

SMTP Server: 10.61.10.8:25
Connect Encryption (TLS): No Encryption
Validate Server Certificate (TLS):
SMTP Authentication Type: Basic Auth with SMTP

Color Page 99

Protocols (cont.)

Bonjour:	Xerox AltaLink C8270 Color MFP (A2:2)
Bonjour Printer Name:	Enabled
HTTP:	80
Port Number:	Yes
Force Traffic over Secure Connection (H...):	443
Secure HTTP Port Number:	Manual
Proxy Server:	10.177.8.91:8080
Proxy Server Address:	Enabled
IPP:	IPP and Secure IPPS
Secure IPP Mode:	http://10.61.16.12:631
IPP Network Path:	
SNMP:	Enabled
SNMP v1/v2:	Disabled
SNMP v3:	Enabled
LPR/LPD:	Enabled
Port Number:	515
PDL Switching:	Disabled
PDL Banner Override:	Disabled
Raw IP Printing:	Enabled
Port Number 1:	9100
Buffering Method:	Disabled
Send to Job's Printer:	Job
PDL Switching:	Disabled
LDAP:	
LDAP Server 1 Friendly Name:	
LDAP Server 1 Primary LDAP Address:	0.0.0.0:389
LDAP Server 1 Alternate LDAP Address:	0.0.0.0:389
LDAP Server 1 Search Directory Root:	
LDAP Server 1 Secure Connection (LDA...):	Disabled
LDAP Server 1 Validate Server Certificate...	Disabled
SMTP:	
SMTP Server:	10.61.10.8:25
Enabled Encryption (TLS):	Not Enabled
Validate Server Certificate (LDA...):	
Max Mailbox Size (KB):	10240
Number of Fragments:	1
Total Job Size (KB):	300000
Job Splitting Boundary:	Page Boundary
Credentials for Auto E-mails:	None
Credentials for Walkup User:	None
SMTP Authentication Type:	Basic Auth with SMTP
POP3:	
POP3 Server:	0.0.0.0:110
POP3 Secure Connection (TLS):	Disabled
Enable Address:	
POP3 Validate Server Certificate:	
Incoming E-mail cover sheet:	Enabled
NTP:	Enabled
Primary Server:	0.0.0.0:123
Alternate Server:	0.0.0.0:123
SLP:	Disabled
FTP Client:	Disabled
FTP Client Mode:	Passive
Web Services on Device:	Enabled
WS-Discovery:	Enabled
WS-Discovery Multicast:	Enabled
WS-Print:	Enabled
WS-Scan:	Enabled
Web Services:	
Job Management Extension:	Enabled
Device Configuration:	Enabled
Secure Submission:	Enabled
Scan Workflow Management:	Enabled
User Interface Configuration:	Enabled
FTP Proxy Configuration:	Disabled
Yottaa Server Access:	Disabled
EIP SNMP Configuration:	Enabled
Print Submission:	Enabled
Mass Storage Access:	Enabled
Authentication & Accounting Configur...	Enabled
Export Audit Log:	Enabled
Trellix Embedded Control:	Enabled

Apps

Printing

Banner Sheet:	Disabled
Sys/Start Job:	Disabled
Delete Held Jobs After:	3 Day(s) 0 Hour(s) 0 Minute(s)
Error Sheets:	Enabled
Paper Substitution:	Enabled
Tray Priority:	1,2,3,4,5
Default Copies:	1
Default Job Type:	Normal Print
Default Paper Size:	x=8.50 inches, y=11.00 inches
Default Paper Color:	White
Default 2 Sided Printing:	1 Sided
Default Output Tray:	Main Tray
Default Output Color:	Color
Default Collated Sets:	Enabled
Default Stapling:	Not Available
Offsetting Between Jobs:	Offset Between Jobs
PostScript	Installed
Level:	3
Image Quality:	Standard
PCL	
Version:	6
Pitch Size:	10.00
Print Size:	12.00
Font Name:	Courier
Lines Per Page:	60
Custom Color Tables:	Enabled
Label:	Not Installed
Fax:	Not Present
Fax Line 1:	

Server Fax:

Enabled	Enabled
Delay Start:	Disabled
Repository Protocol:	SMB
Repository Server:	10.61.23.0:445
Repository Document Path:	/
Workflow Scanning:	Enabled
Default Repository Server:	0.0.0.0
Default Repository Document Path:	Device
Default Repository Login Credentials:	

Alt1 Repository Login Credentials:	Device
Workflow Pool Protocol:	FTP
Workflow Pool Server:	0.0.0.0
Workflow Pool Path:	

Email:

Default From Address:	sysadmin@msd@xerox.com
Confirmation Sheet:	On
Auto Send to Self:	Disabled
E-mail Security:	Disabled
Scan to Mailbox:	Enabled
View Mailboxes by Default:	46924 MB
Storage Capacity (MB):	

Cleanup of Public Folders:	Enabled
Cleanup of Created Folders:	Enabled

Scan to Home:

Friendly Name:	
Auto Create Subdir:	Disabled
Auto Create User Name Dir:	Disabled
Scan To:	Disabled
Print From:	Enabled
Saved Jobs for Reprint:	Enabled
Print From MailBox:	Disabled

Accounting

Accounting Mode: None
Network Accounting: Disabled

Security**Authentication Configuration**

Machine UI Authentication: Locally on the Device
Home: Unlocked
Jobs: Unlocked
Device: Unlocked
Device Website Authentication: Locally on the Device
Authorization: Locally on the Device
Retrieve E-mail from LDAP: Enabled
Kerberos: Kerberos

Authentication Server:

Kerberos Primary Realm: 0.0.0.88
Kerberos Primary Address: 0.0.0.88
Kerberos Alt 1 Realm:
Kerberos Alt 1 Address:
SMB NT Domain:
SMB Alt 1 NT Domain:

SmartCard Ctrl Domain:
SmartCard OCSP URL:
Card Reader Upgrade Policy: Enabled
Card Reader Firmware Version:

Secure Access Server: 0.0.0.44
Secure Access Path:

Audit Log:

IP Sec: Enabled
IP Filtering: Disabled
Security Certificate: Disabled

Machine Certificate: Enabled
Device Certificate: Disabled

802.1x:

Job Data Removal: Disabled

Scheduled: Disabled

Scheduled Frequency: Disabled

FIPS 140-3: Disabled

TLS: TLS 1.2 and TLS 1.3

Trellix Embedded Control:

Enhanced Security

Extensible Service Setup

Widget Version: v2.5.04 (9/20/24) 123