

Common User Data

Machine Name:	Xerox VersaLink C415 Color MFP (46:6...
Pv4 Address:	10.61.16.35
Machine Serial Number:	5334205608
ax Line1:	
Machine URL:	https://10.61.16.35
Machine Activation Date:	Jan 01, 2021 05:33:40
Black Impressions:	306
Color Impressions:	6
Total Impressions:	312

Machine Profile

Xerox Asset Tag:	
Customer Asset Tag:	
Service Phone Number:	
Customer Support Number:	
Supplies Phone Number:	
Recycling Phone Number:	
System Administrator:	Not set
Machine Location:	machine location not set

Managed By

Primary MB Server:

Machine Hardware

ax Card:	Not Present
ax Memory Size:	0 MB
oreign Interface Card:	not present
evice RAM Size:	1984 MB
evice Storage Size:	used=3165MB/total=14004MB (eMMC)
PC Memory Size:	187 MB
roductivity Kit:	Not Installed
inisher Type:	Simple Catch Tray
inisher Punch:	None
inisher Folder:	not present
ulti-feed Detection Kit:	Not Installed

General Setup

emote Services:	Enabled
emote Software Download:	Enabled
emote Services Trans. Time:	08:46
erox Workplace Cloud	Enabled
-mail Alerts:	Disabled
ervice Plan:	Plan Activated
eographic Region:	unknown
MT Offset:	+05:30
loning Installation	Allowed (Encrypted Files Only)
ile Sharing	Enabled
3IG2	Lossless
Energy Saver	
Deep Sleep:	Disabled
Energy Saver Mode:	Job Activated
Smart Proximity Sensor	Not Available
Wake on Arrival:	
Sleep on Departure:	

Software Versions

evice Software:	123.028.005.27600
atch Version:	None
etwork Controller:	123.028.27600
II Panel Firmware:	6.2
arking Engine:	237.003
ocument Feeder:	237.003
inisher:	000.000.000
ax:	000.000.000
canner:	237.003
Machine Upgrades:	Allowed
Last Successful Upgrade:	October 6, 2025 16:33:13

Media Trays

ray 1:	Plain, White and Letter (8.5 x 11")
ray 2:	Plain, White and A4 (210 x 297 mm)
ray 3:	Plain, White and A4 (210 x 297 mm)
ray 4:	Plain, White and x=8.27 inches, y=8....
Manual Feeder:	Plain, White and Letter (8.5 x 11")

Installed Options

S:	Installed
----	-----------

Connectivity

Mobile Workflows

AirPrint Printing:	Enabled
Mopria Printing:	Enabled
AirPrint / Mopria Scanning	Enabled
Authentication Required:	Disabled
Physical Connections	
USB Settings	
USB Type A Ports	All Enabled
USB Type B Port	Enabled
Wired:	Enabled
Ethernet MAC Address:	78:8c:77:46:60:59
Ethernet Speed/Duplex Setting:	auto
Wireless:	Disabled
Wireless MAC Address:	
Network Name (SSID):	
BSSID:	
Security Mode:	
Encryption Algorithm:	
Status:	
Wi-Fi Direct:	Enabled
Wireless Hardware:	Not Installed
Wi-Fi Protected Setup™ (WPS) Name:	
Access Point (SSID):	
Show Password on Device Touch Screen:	
NFC:	Enabled
iBeacon (Bluetooth®) for AirPrint Di...	Enabled
iBeacon Hardware:	Not Installed
Bluetooth Device Address:	
iBeacon IP Address:	

Protocols

TCP/IPv4:	Enabled
IPv4 Address:	10.61.16.35
Subnet Mask:	255.255.255.0
Router/Gateway:	10.61.16.1
Automatic Addressing:	DHCP
DHCP Server:	
DHCP Lease Expiration:	
BOOTP Broadcast:	Disabled
Self Assigned Address State:	Enabled
Self Assigned Address:	

TCP/IPv6:

Link Local Address:	
Use Router Supplied Prefix:	
Stateless Global Address 1:	
Stateless Global Address 2:	
Manual Address:	
DHCP Addressing:	
DHCP Address:	
Default Gateway:	
DUID (DHCP Unique Identifier):	

DNS Settings:

Requested Host Name:	XRX788C77466059
Verified Host Name:	
Requested Domain Name:	
Verified Domain Name:	
Multicast DNS:	Enabled
Release DHCP Leases and DNS Registrati...	Disabled
Primary DNS Server:	10.61.7.16
Prefer IPv6 DNS over IPv4:	Enabled

Bonjour:

Bonjour Printer Name:	Xerox VersaLink C415 Color MFP (46:6...
HTTP:	Enabled
Force Traffic over Secure Connection (H...	Yes
IPP	Enabled

SNMP

SNMP v1/v2:	Enabled
SNMP v3:	Disabled

LPR/LPD:

Raw IP Printing: Enabled

LDAP

LDAP Server 1 Primary LDAP Address:	0.0.0.0:389
LDAP Server 1 Search Directory Root:	
LDAP Server 1 Secure Connection (LDA...	Disabled
LDAP Server 1 Validate Server Certificate...	Disabled

SMTP

SMTP Server:	10.61.10.8:25
Connect Encryption (TLS):	No Encryption
Validate Server Certificate (TLS):	
SMTP Authentication Type:	Basic Auth with SMTP

Protocols (cont.)

POP3	
POP3 Server:	0.0.0.0:110
POP3 Secure Connection (TLS):	Disabled
POP3 Validate Server Certificate:	
E-mail Address:	
NTP:	Disabled
FTP Client:	Enabled
FTP Client Mode:	Passive
Web Services on Device:	Enabled

Apps

Printing

Banner Sheet:	Enabled
Error Sheets:	Enabled
Paper Substitution:	Enabled
Tray Priority:	1,2,3,4,5
Archival Marking Mode	Off
PostScript	Installed
Level:	3
Version:	3021.101
PCL	
Version:	6
Font Name:	Courier
Custom Color Tables	Enabled
Label:	Not Installed
Fax:	Not Present

Fax Line1:	
Fax Line2:	
Server Fax:	Enabled
Repository Protocol:	SMB
Repository Server:	0.0.0.0:0
Repository Document Path:	

Workflow Scanning:

Email:	Enabled
Scan to Mailbox:	Enabled
Storage Capacity (MB):	672 MB
Storage Used (MB):	50 MB
Cleanup of Public Folders:	Disabled
Cleanup of Created Folders:	Disabled
Cleanup Time:	Daily

Scan to Home:

Scan To:	Disabled
Cloud Services:	Enabled
Print From:	Disabled
Saved Jobs for Reprint:	Enabled
Print From USB:	Enabled
Print From MailBox:	Disabled
Cloud Services:	Disabled

Accounting

Accounting Mode:	None
Network Accounting:	Disabled

Security

Authentication Configuration

Machine UI Authentication:	Locally on the Device
Home:	Unlocked
Jobs:	Unlocked
Device:	Unlocked
Device Website Authentication:	Locally on the Device
Authorization:	Locally on the Device
Retrieve E-mail from LDAP:	Enabled

Authentication Server:

Xerox Secure Access:	Kerberos
Audit Log:	Disabled
IP Sec:	Enabled
IP Filtering:	Disabled

Security Certificates

Machine Certificate:	Signed
Root Certificates Installed:	54
802.1x:	Disabled

Job Data Removal:

Scheduled:	Disabled
FIPS 140-3:	Disabled

TLS:	TLS 1.2 and TLS 1.3
TLS Hash:	SHA-1, SHA-256 and above
Trellix Embedded Control:	Enhanced Security

Common User Data

Machine Name:	Xerox VersaLink C415 Color MFP (46:6...
IPv4 Address:	10.61.16.35
Machine Serial Number:	5334205608
Fax Line1:	
Machine URL:	https://10.61.16.35
Machine Activation Date:	Jan 01, 2021 05:33:40
Black Impressions:	309
Color Impressions:	8
Total Impressions:	317

Machine Profile

Xerox Asset Tag:	
Customer Asset Tag:	
Service Phone Number:	
Customer Support Number:	
Supplies Phone Number:	
Recycling Phone Number:	
System Administrator:	Not set
Machine Location:	machine location not set
Managed By	
Primary MB Server:	

Machine Hardware

Fax Card:	Not Present
Fax Memory Size:	0 MB
Foreign Interface Card:	not present
Device RAM Size:	1984 MB
Device Storage Size:	used=3471MB/total=14004MB (eMMC)
EPC Memory Size:	187 MB
Productivity Kit:	Not Installed
Finisher Type:	Simple Catch Tray
Finisher Punch:	None
Finisher Folder:	not present
Multi-feed Detection Kit:	Not Installed

General Setup

Remote Services:	Enabled
Remote Software Download:	Enabled
Remote Services Trans. Time:	08:46
Xerox Workplace Cloud	Enabled
E-mail Alerts:	Disabled
Service Plan:	Plan Activated
Geographic Region:	unknown
Startup Config Report:	Disabled
GMT Offset:	+05:30
Cloning Installation	Allowed (Encrypted Files Only)
Allow Print Submission of Clone Files:	Enabled
File Sharing	Enabled
JBIG2	Lossless

Energy Saver

Deep Sleep:	Disabled
Energy Saver Mode:	Job Activated
Sleep Mode Timer:	120 minutes
Auto-Off:	Disabled

Software Versions

Device Software:	123.028.005.27600
Patch Version:	None
Network Controller:	123.028.27600
UI Panel Firmware:	6.2
User Interface:	123.028.27600
Marking Engine:	237.003
Copy Controller:	123.028.27600
Document Feeder:	237.003
Finisher:	000.000.000
Fax:	000.000.000
OS:	237.003
Scanner:	237.003
Software Upgrade:	006.001
ALTBOOT Software Upgrade:	006.001
Tray 2:	A16.84_B2.3
Tray 3:	A16.85_B2.3
Tray 4:	A16.85_B2.3
Machine Upgrades:	Allowed
Last Successful Upgrade:	October 6, 2025 16:33:13
Scheduled Auto Upgrades:	Disabled
Auto Upgrade Start Time:	Daily
Auto Upgrade Server:	0.0.0.0:21

Media Trays

Tray 1:	Plain, White and Letter (8.5 x 11")
Tray 2:	Plain, White and A4 (210 x 297 mm)
Tray 3:	Plain, White and A4 (210 x 297 mm)
Tray 4:	Plain, White and x=8.27 inches, y=8...
Manual Feeder:	Plain, White and Letter (8.5 x 11")

Connectivity

Mobile Workflows

AirPrint Printing:	Enabled
Mopria Printing:	Enabled
AirPrint / Mopria Scanning	Enabled
Authentication Required:	Disabled
Universal Print:	Disabled
Universal Print Registration Status:	Not Registered
Physical Connections	
USB Settings	
USB Type A Ports	All Enabled
USB Type B Port	Enabled
Connection Timeout	5 seconds
Wired:	Enabled
Ethernet MAC Address:	78:8c:77:46:60:59
Ethernet Speed/Duplex Setting:	auto
Wireless:	Disabled
Wireless MAC Address:	
Network Name (SSID):	
BSSID:	
Security Mode:	
Encryption Algorithm:	
Status:	
Wi-Fi Direct:	Enabled
Wireless Hardware:	Not Installed
Wi-Fi Protected Setup™ (WPS) Name:	
Connection Method:	
Subnet Prefix Address:	
Access Point (SSID):	
Show Password on Device Touch Screen:	
NFC:	Enabled
iBeacon (Bluetooth®) for AirPrint Di...	Enabled
iBeacon Hardware:	Not Installed
Bluetooth Device Address:	
iBeacon IP Address:	

Protocols

TCP/IPV4:	Enabled
IPv4 Address:	10.61.16.35
Subnet Mask:	255.255.255.0
Router/Gateway:	10.61.16.1
Automatic Addressing:	DHCP
DHCP Server:	
DHCP Lease Expiration:	
BOOTP Broadcast:	Disabled
Self Assigned Address State:	Enabled
Self Assigned Address:	

TCP/IPV6:	Disabled
Link Local Address:	
Use Router Supplied Prefix:	
Stateless Global Address 1:	
Stateless Global Address 2:	
Manual Address:	
DHCP Addressing:	
DHCP Address:	
Default Gateway:	
DUID (DHCP Unique Identifier):	

DNS Settings:	
Requested Host Name:	XRX788C77466059
Verified Host Name:	
Requested Domain Name:	
Verified Domain Name:	
Multicast DNS:	Enabled
Release DHCP Leases and DNS Registrati...	Disabled
Primary DNS Server:	10.61.7.16
Alternate DNS Server 1:	10.61.10.6
Alternate DNS Server 2:	10.61.7.15
DNS Connection Timeout:	5
Append Device Domain:	Enabled
Append Parent Domains:	Disabled
DNS Domain Search List:	XEROXQA.COM.
Prefer IPv6 DNS over IPv4:	Enabled

Installed Options

PS:	Installed
-----	-----------

Protocols (cont.)

Bonjour:

Bonjour Printer Name:	Xerox VersaLink C415 Color MFP (46:6...
HTTP:	Enabled
Port Number:	80
Force Traffic over Secure Connection (H...	Yes
Secure HTTP Port Number:	443
Proxy Server:	Disabled
Proxy Server Address:	0.0.0.0:8080
IPP	Enabled
Secure IPP Mode:	IPP and Secure IPPS
IPP Network Path:	http://10.61.16.35:631

SNMP

SNMP v1/v2:	Enabled
SNMP v3:	Disabled

LPR/LPD:

Port Number:	Enabled
PDL Switching:	515
PDL Banner Override:	Disabled

Raw IP Printing:

Port Number 1:	Enabled
Bidirectional:	9100
End of Job Timeout:	Disabled
PDL Switching:	300
	Disabled

LDAP

LDAP Server 1 Friendly Name:	
LDAP Server 1 Primary LDAP Address:	0.0.0.0:389
LDAP Server 1 Alternate LDAP Address:	0.0.0.0:389
LDAP Server 1 Search Directory Root:	
LDAP Server 1 Secure Connection (LDA...	Disabled
LDAP Server 1 Validate Server Certificate...	Disabled

SMTP

SMTP Server:	10.61.10.8:25
Connect Encryption (TLS):	No Encryption
Validate Server Certificate (TLS):	
Max Message Size (KB):	10240
Number of Fragments:	1
Total Job Size (KB):	300000
Job Splitting Boundary:	Page Boundary
Credentials for Auto E-mails:	None
Credentials for Walkup User:	None
SMTP Authentication Type:	Basic Auth with SMTP

POP3

POP3 Server:	0.0.0.0:110
POP3 Secure Connection (TLS):	Disabled
E-mail Address:	
POP3 Validate Server Certificate:	
Receipt of E-mail via POP3:	Disabled
Send Confirm on Request:	Enabled
Incoming E-mail cover sheet:	Enabled

NTP:

Primary Server:	0.0.0.0:123
Alternate Server:	0.0.0.0:123

SLP:

FTP Client:	Disabled
FTP Client Mode:	Enabled

Web Services on Device:

WS-Discovery:	Passive
WS-Discovery Multicast:	Enabled
WS-Print:	Enabled
WS-Scan:	Enabled

Web Services

Copy Submission:	Enabled
Digital Certificate Management and Securi...	Enabled
Extensible Service Registration:	Enabled
Job Limits:	Enabled
Job Management Extension:	Enabled
Device Configuration:	Enabled
Scan Submission:	Enabled
Scan Workflow Management:	Enabled
Session Data:	Enabled
User Interface Configuration:	Enabled
EIP Proxy Configuration:	Enabled
Xerox Secure Access:	Disabled
EIP SNMP Configuration:	Enabled
Print Submission:	Enabled
Scan Template Mgmt:	Enabled
Mass Storage Access:	Enabled
Card Reader Access:	Enabled
Authentication & Accounting Configur...	Enabled
Export Audit Log:	Enabled
Trellix Embedded Control:	Enabled

Apps

Printing

Banner Sheet:	Enabled
Sys/Start Job:	Disabled
Delete Held Jobs After:	3 Day(s) 0 Hour(s) 0 Minute(s)
Error Sheets:	Enabled
Paper Substitution:	Enabled
Tray Priority:	1,2,3,4,5
Default Copies:	1
Default Job Type:	Normal Print
Default Paper Size:	x=8.50 inches, y=11.00 inches
Default Paper Color:	White
Default 2 Sided Printing:	2 Sided
Default Output Tray:	Center Tray
Default Output Color:	Color
Default Collated Sets:	Enabled
Default Stapling:	Not Available
Offsetting Between Jobs:	No Offset Between Jobs
Archival Marking Mode	Off
PostScript	Installed
Level:	3
Version:	3021.101
Image Quality:	Enhanced

PCL

Version:	6
Pitch Size:	10.00
Point Size:	12.00
Font Name:	Courier
Lines Per Page:	60
Custom Color Tables	Enabled
Label:	Not Installed
Fax:	Not Present

Fax:

Fax Line1:	
Fax Line2:	

Server Fax:

Confirmation Sheet:	Enabled
Delay Start:	Errors Only
Repository Protocol:	Disabled
Repository Server:	SMB
Repository Document Path:	0.0.0.0:0

Workflow Scanning:

Confirmation Sheet:	Enabled
Default Repository Protocol:	Errors Only
Default Repository Server:	SMB
Default Repository Document Path:	0.0.0.0:0
Default Repository Login Credentials:	
Alt1 Repository Protocol:	Device
Alt1 Repository Server:	SMB
Alt1 Repository Document Path:	0.0.0.0:0
Alt1 Repository Login Credentials:	
Workflow Pool Protocol:	Device
Workflow Pool Server:	SMB
Workflow Pool Path:	0.0.0.0:0

Email:

Default From Address:	Enabled
Confirmation Sheet:	Habibunnisa@xeroxqa.com
Auto Send to Self:	Errors Only
E-mail Security:	Disabled

Scan to Mailbox:

View Mailboxes by Default:	Enabled
Storage Capacity (MB):	Enabled
Storage Used (MB):	672 MB
Cleanup of Public Folders:	50 MB
Cleanup of Created Folders:	Disabled
Cleanup Time:	Disabled
Daily	Disabled

Scan to Home:

Friendly Name:	
Workflow Name:	
Auto Create Subdir:	Disabled
Append User Name to Path:	Disabled
Auto Create User Name Dir:	Disabled

Scan To:

Cloud Services:	Enabled
-----------------	---------

Print From:

Saved Jobs for Reprint:	Enabled
Print From USB:	Enabled
Print From MailBox:	Enabled
Cloud Services:	Disabled

Accounting

Accounting Mode: None
Network Accounting: Disabled

Security

Authentication Configuration

Machine UI Authentication: Locally on the Device
Home: Unlocked
Jobs: Unlocked
Device: Unlocked
Device Website Authentication: Locally on the Device
Authorization: Locally on the Device
Retrieve E-mail from LDAP: Enabled
Authentication Server: Kerberos

Kerberos Primary Realm:
Kerberos Primary Address: 0.0.0.0:88
Kerberos Alt 1 Realm:
Kerberos Alt 1 Address: 0.0.0.0:88
SMB NT Domain:
SMB Alt 1 NT Domain:
Smartcard Ctrl Server: 0.0.0.0:443
Smartcard Ctrl Domain:
SmartCard OCSP URL:
Card Reader Upgrade Policy: Enabled
Card Reader Firmware Version:

Xerox Secure Access:

Secure Access Server: Disabled
Secure Access Path: 0.0.0.0:443

Audit Log:

IP Sec: Enabled
IP Filtering: Disabled
Disabled

Security Certificates

Machine Certificate: Signed
Root Certificates Installed: 54
802.1x: Disabled

Job Data Removal:

Scheduled: Disabled
Scheduled Frequency:

FIPS 140-3:

TLS: Disabled
TLS Hash: TLS 1.2 and TLS 1.3
SHA-1, SHA-256 and above
Trellix Embedded Control: Enhanced Security

Extensible Service Setup

Third Generation Browser: X3G_3.24.23_2.40.5_012_01.00.00
Widget Version: v1.3.17 c8 20140613
Widget Version: v2.5.04 g9 20240123

