

IPv4 Disable

Common User Data

Machine Name: Xerox VersaLink B620 Printer (FE:F6:79)
 Machine Serial Number: 5320705462
 Machine Activation Date: Jul 17, 2025 18:33:33
 Total Impressions: 6646

Machine Profile

Xerox Asset Tag:
 Customer Asset Tag:
 Service Phone Number:
 Customer Support Number:
 Supplies Phone Number:
 System Administrator:
 Machine Location: Not set
 machine location not set

Managed By

Primary MB Server:

Machine Hardware

Foreign Interface Card: not present
 Device RAM Size: 1984 MB
 Device Storage Size: used=2687MB/total=0MB (eMMC)
 EPC Memory Size: 187 MB
 Productivity Kit: used=74MB/total=0MB (HDD)
 Finisher Type: Simple Catch Tray
 Finisher Punch: None
 Finisher Folder: not present

General Setup

Remote Services: Enabled
 Remote Software Download: Enabled
 Remote Services Trans. Time: 17.27
 Xerox Workplace Cloud: Enabled
 E-mail Alerts: Disabled
 Service Plan: Sold
 Geographic Region: unknown
 GMT Offset: +05:30
 Cloning Installation: Allowed (Encrypted Files Only)
 File Sharing: Enabled
 iBIG2: Lossless

Energy Saver

Deep Sleep: Enabled
 Energy Saver Mode: Job Activated

Smart Proximity Sensor

Wake on Arrival: Not Available
 Sleep on Departure:

Software Versions

Device Software: 123.027.005.24410
 Patch Version: None
 Network Controller: 123.027.24410
 UI Panel Firmware: 6.2
 Marking Engine: 237.002
 Finisher: 000.000.000

Machine Upgrades:

Last Successful Upgrade: September 9, 2025 16:04:26

Media Trays

Tray 1: Plain, White and A4 (210 x 297 mm)
 Bypass Tray: Plain, White and Letter (8.5 x 11")

Installed Options

PS: Installed

Connectivity

Mobile Workflows

AirPrint Printing: Enabled
 Mopria Printing: Enabled

Physical Connections

USB Settings
 USB Type A Ports: All Enabled
 USB Type B Port: Enabled
Wired:
 Ethernet MAC Address: Enabled
 Ethernet Speed/Duplex Setting: 9c:93:4e:fe:f6:79
 auto
 Disabled

Wireless:

Wireless MAC Address:
 Network Name (SSID):
 BSSID:
 Security Mode:
 Encryption Algorithm:
 Status:

Wi-Fi Direct: Enabled
 Wireless Hardware: Not Installed

Wi-Fi Protected Setup™ (WPS) Name:
 Access Point (SSID):
 Show Password on Device Touch Screen:

NFC: Enabled
 iBeacon (Bluetooth®) for AirPrint Di...: Enabled
 iBeacon Hardware: Not Installed
 iBeacon Device Address:
 iBeacon IP Address:

Protocols



TCP/IPV4:

IPv4 Address: Disabled
 Subnet Mask:
 Router/Gateway:
 Automatic Addressing:
 DHCP Server:
 DHCP Lease Expiration:
 BOOTP Broadcast:
 Self Assigned Address State:
 Self Assigned Address:

TCP/IPV6:

Link Local Address: Enabled
 fe80::9e93:4eff:fefe:f679
 Use Router Supplied Prefix: Enabled
 Stateless Global Address 1: 2403:0:22b:4:9e93:4eff:fefe:f679
 Stateless Global Address 2:
 Manual Address:
 DHCP Addressing: Use DHCP as directed by a router
 DHCP Address: 2403:0:22b:4:753:a076:6045:187d
 Default Gateway: fe80::4e42:1eff:fe9e:7967
 DUID (DHCP Unique Identifier): 000300019c934efef679

DNS Settings:

Requested Host Name: XRX9C934EFEF679
 Verified Host Name:
 Requested Domain Name:
 Verified Domain Name:
 Multicast DNS: Enabled
 Release DHCP Leases and DNS Registrati...: Disabled
 Primary DNS Server: 2403:0:22b:4:7006:5a52:f43b:a95f
 Prefer IPv6 DNS over IPv4: Enabled

Bonjour:

Bonjour Printer Name: Xerox VersaLink B620 Printer (FE:F6:79)

HTTP:

Force Traffic over Secure Connection (H...: Enabled
 IPP: Yes
 Enabled

SNMP

SNMP v1/v2: Enabled
 SNMP v3: Disabled

LPR/LPD:

Enabled

Raw IP Printing:

Enabled

LDAP

LDAP Server 1 Primary LDAP Address: 0.0.0.0:389
 LDAP Server 1 Search Directory Root:
 LDAP Server 1 Secure Connection (LDA...: Disabled
 LDAP Server 1 Validate Server Certificate...: Disabled

SMTP

SMTP Server: 0.0.0.0:25
 Connect Encryption (TLS): No Encryption
 Validate Server Certificate (TLS):

Protocols (cont.)

POP3	
POP3 Server:	0.0.0.0:110
POP3 Secure Connection (TLS):	Disabled
POP3 Validate Server Certificate:	
E-mail Address:	
NTP:	Disabled
FTP Client:	Enabled
FTP Client Mode:	Passive
Web Services on Device:	Enabled

Apps**Printing**

Banner Sheet:	Enabled
Error Sheets:	Enabled
Paper Substitution:	Disabled
Tray Priority:	1,5
Archival Marking Mode	Off
PostScript	Installed
Level:	3
Version:	3021.101
PCL	
Version:	6
Font Name:	Courier
Custom Color Tables	Enabled
Label:	Not Installed
Print From:	Enabled
Saved Jobs for Reprint:	Enabled
Print From USB:	Enabled
Cloud Services:	Disabled

Accounting

Accounting Mode:	None
Network Accounting:	Disabled

Security**Authentication Configuration**

Machine UI Authentication:	Locally on the Device
Home:	Unlocked
Jobs Pathway:	Unlocked
Printer Pathway:	Unlocked
Device Website Authentication:	Locally on the Device
Authorization:	Locally on the Device

Authentication Server:**Xerox Secure Access:****Audit Log:****IP Sec:****IP Filtering:****Security Certificates**

Machine Certificate:	Signed
Root Certificates Installed:	54
802.1x:	Disabled

Image Overwrite

Immediate:	Installed/Enabled
Scheduled:	Disabled
FIPS 140-3:	Disabled

TLS:

TLS Hash:	TLS 1.2 and TLS 1.3
Trellix Embedded Control:	SHA-1, SHA-256 and above
	Enhanced Security

IPv4 Disable



Common User Data

Machine Name: Xerox VersaLink B620 Printer (FE:F6:79)
Machine Serial Number: 5320705462
Machine Activation Date: Jul 17, 2025 18:33:33
Total Impressions: 6648

Machine Profile

Xerox Asset Tag:
Customer Asset Tag:
Service Phone Number:
Customer Support Number:
Supplies Phone Number:
System Administrator: Not set
Machine Location: machine location not set
Managed By
Primary MB Server:

Machine Hardware

Foreign Interface Card: not present
Device RAM Size: 1984 MB
Device Storage Size: used=2688MB/total=0MB (eMMC)
EPC Memory Size: 187 MB
Productivity Kit: used=75MB/total=0MB (HDD)
Finisher Type: Simple Catch Tray
Finisher Punch: None
Finisher Folder: not present

General Setup

Remote Services: Enabled
Remote Software Download: Enabled
Remote Services Trans. Time: 17:27
Xerox Workplace Cloud: Enabled
E-mail Alerts: Disabled
Service Plan: Sold
Geographic Region: unknown
Startup Config Report: Enabled
GMT Offset: +05:30
Cloning Installation: Allowed (Encrypted Files Only)
Allow Print Submission of Clone Files: Enabled
File Sharing: Enabled
JBIG2: Lossless

Energy Saver

Deep Sleep: Enabled
Energy Saver Mode: Job Activated
Sleep Mode Timer: 120 minutes
Auto-Off: Disabled

Software Versions

Device Software: 123.027.005.24410
Patch Version: None
Network Controller: 123.027.24410
UI Panel Firmware: 6.2
User Interface: 123.027.24410
Marking Engine: 237.002
Finisher: 000.000.000
OS: 237.002
Software Upgrade: 005.016
ALTBOOT Software Upgrade: 005.016

Machine Upgrades

Last Successful Upgrade: September 9, 2025 16:04:26
Scheduled Auto Upgrades: Disabled
Auto Upgrade Start Time: Daily
Auto Upgrade Server: 0.0.0.21

Media Trays

Tray 1: Plain, White and A4 (210 x 297 mm)
Bypass Tray: Plain, White and A4 (210 x 297 mm)

Connectivity

Mobile Workflows

AirPrint Printing: Enabled
Mopria Printing: Enabled
Universal Print: Disabled
Universal Print Registration Status: Not Registered

Physical Connections

USB Settings
USB Type A Ports: All Enabled
USB Type B Port: Enabled
Connection Timeout: 5 seconds

Wired:

Ethernet MAC Address: 9c:93:4e:fe:f6:79
Ethernet Speed/Duplex Setting: auto
Wireless: Disabled

Wireless:

Wireless MAC Address:
Network Name (SSID):
BSSID:
Security Mode:
Encryption Algorithm:
Status:

Wi-Fi Direct:

Wireless Hardware: Enabled
Wi-Fi Protected Setup™ (WPS) Name: Not Installed
Connection Method:
Subnet Prefix Address:
Access Point (SSID):
Show Password on Device Touch Screen:

NFC:

iBeacon (Bluetooth®) for AirPrint Di...: Enabled
iBeacon Hardware: Enabled
Bluetooth Device Address: Not Installed
iBeacon IP Address:

Protocols

TCP/IPv4: Disabled

IPv4 Address:
Subnet Mask:
Router/Gateway:
Automatic Addressing:
DHCP Server:
DHCP Lease Expiration:
BOOTP Broadcast:
Self Assigned Address State:
Self Assigned Address:

TCP/IPv6:

Link Local Address: Enabled
fe80::9e93:4eff:fe:f679
Use Router Supplied Prefix: Enabled
Stateless Global Address 1: 2403:0:22b:4:9e93:4eff:fe:f679
Stateless Global Address 2:
Manual Address:
DHCP Addressing: Use DHCP as directed by a router
DHCP Address: 2403:0:22b:4:753:a076:6045:187d
Default Gateway: fe80::4e42:1eff:fe9e:7967
DUID (DHCP Unique Identifier): 000300019c934ef679

DNS Settings:

Requested Host Name: XRXC934EFFF679
Verified Host Name:
Requested Domain Name:
Verified Domain Name:
Multicast DNS: Enabled
Release DHCP Leases and DNS Registrati...: Disabled
Primary DNS Server: 2403:0:22b:4:7006:5a52:f43b:a95f
Alternate DNS Server 1:
Alternate DNS Server 2:
DNS Connection Timeout: 5
Append Device Domain: Enabled
Append Parent Domains: Disabled
DNS Domain Search List:
Prefer IPv6 DNS over IPv4: Enabled

Installed Options

PS: Installed

Protocols (cont.)

Bonjour:
 Bonjour Printer Name: Xerox VersaLink B620 Printer (FE:F6:79)
HTTP:
 Port Number: 80
 Force Traffic over Secure Connection (H...): Yes
 Secure HTTP Port Number: 443
 Proxy Server: Disabled
 Proxy Server Address: 0.0.0.0:8080
 IPP
 Secure IPP Mode: IPP and Secure IPPS
 IPP Network Path: http://:631

SNMP
 SNMP v1/v2: Enabled
 SNMP v3: Disabled

LPR/LPD:
 Port Number: 515
 PDL Switching: Disabled
 PDL Banner Override: Disabled

Raw IP Printing:
 Port Number 1: 9100
 Bidirectional: Disabled
 End of Job Timeout: 300
 PDL Switching: Disabled

LDAP
 LDAP Server 1 Friendly Name:
 LDAP Server 1 Primary LDAP Address: 0.0.0.0:389
 LDAP Server 1 Alternate LDAP Address: 0.0.0.0:389
 LDAP Server 1 Search Directory Root:
 LDAP Server 1 Secure Connection (LDA...): Disabled
 LDAP Server 1 Validate Server Certificate...: Disabled

SMTP
 SMTP Server: 0.0.0.0:25
 Connect Encryption (TLS): No Encryption
 Validate Server Certificate (TLS):
 Max Message Size (KB): 10240
 Number of Fragments: 1
 Total Job Size (KB): 300000
 Job Splitting Boundary: Page Boundary
 Credentials for Auto E-mails: None
 SMTP Authentication Type: Basic Auth with SMTP

POP3
 POP3 Server: 0.0.0.0:110
 POP3 Secure Connection (TLS): Disabled
 E-mail Address:
 POP3 Validate Server Certificate:
 Receipt of E-mail via POP3: Disabled
 Send Confirm on Request: Enabled
 Incoming E-mail cover sheet: Enabled

NTP:
 Primary Server: [2403:0:22b:4:7006:5a52:f43b:a95f]:123
 Alternate Server: [::]:123

SLP: Disabled

FTP Client: Enabled
 FTP Client Mode: Passive

Web Services on Device: Enabled
 WS-Discovery: Enabled
 WS-Discovery Multicast: Enabled
 WS-Print: Enabled

Web Services
 Digital Certificate Management and Securi...: Enabled
 Extensible Service Registration: Enabled
 Job Limits: Enabled
 Job Management Extension: Enabled
 Device Configuration: Enabled
 Session Data: Enabled
 User Interface Configuration: Enabled
 EIP Proxy Configuration: Enabled
 Xerox Secure Access: Disabled
 EIP SNMP Configuration: Enabled
 Print Submission: Enabled
 Mass Storage Access: Enabled
 Card Reader Access: Enabled
 Authentication & Accounting Configur...: Enabled
 Export Audit Log: Enabled
 Trellix Embedded Control: Enabled

Apps

Printing
 Banner Sheet: Enabled
 Sys/Start Job: Disabled
 Delete Held Jobs After: 3 Day(s) 0 Hour(s) 0 Minute(s)
 Error Sheets: Enabled
 Paper Substitution: Disabled
 Tray Priority: 1,5
 Default Copies: 1
 Default Job Type: Normal Print
 Default Paper Size: x=210mm, y=297mm
 Default Paper Color: White
 Default 2 Sided Printing: 2 Sided
 Default Output Tray: Center Tray
 Default Output Color: Black & White
 Default Collated Sets: Enabled
 Default Stapling: Not Available
 Offsetting Between Jobs: No Offset Between Jobs
 Archival Marking Mode: Off
PostScript
 Level: 3
 Version: 3021.101
 Image Quality: Enhanced

PCL
 Version: 6
 Pitch Size: 10.00
 Point Size: 12.00
 Font Name: Courier
 Lines Per Page: 64
 Custom Color Tables: Enabled
 Label: Not Installed

Print From: Enabled
 Saved Jobs for Reprint: Enabled
 Print From USB: Enabled
 Cloud Services: Disabled

Accounting

Accounting Mode: None
 Network Accounting: Disabled

Security

Authentication Configuration

Machine UI Authentication: Locally on the Device
 Home: Unlocked
 Jobs Pathway: Unlocked
 Printer Pathway: Unlocked
 Device Website Authentication: Locally on the Device
 Authorization: Locally on the Device
 Authentication Server: Kerberos

Authentication Server:

Kerberos Primary Realm:
 Kerberos Primary Address: 0.0.0.0:88
 Kerberos Alt 1 Realm:
 Kerberos Alt 1 Address: 0.0.0.0:88
 SMB NT Domain:
 SMB Alt 1 NT Domain:
 Smartcard Ctrl Server: 0.0.0.0:443
 Smartcard Ctrl Domain:
 SmartCard OCSP URL:
 Card Reader Upgrade Policy: Enabled
 Card Reader Firmware Version:

Xerox Secure Access:

Secure Access Server: Disabled
 Secure Access Path: 0.0.0.0:443

Audit Log:

Audit Log: Enabled

IP Sec:

IP Sec: Disabled

IP Filtering:

IP Filtering: Disabled

Security Certificates

Machine Certificate: Signed

Root Certificates Installed: 54

802.1x: Disabled

Image Overwrite

Immediate: Installed/Enabled

Scheduled: Disabled

Scheduled Frequency:

FIPS 140-3: Disabled

TLS: TLS 1.2 and TLS 1.3

TLS Hash: SHA-1, SHA-256 and above

Trellix Embedded Control: Enhanced Security

Extensible Service Setup

Third Generation Browser: X3G_3.24.23_2,40.5_012_01.00.00

Widget Version: v1.3.17 c8 20140613

Widget Version: v2.5.04 g9 20240123

Common User Data

Machine Name: Xerox VersaLink B620 Printer (FE:F6:79)
IPv4 Address: 10.61.16.207
Machine Serial Number: 5320705462
Machine URL: https://10.61.16.207
Machine Activation Date: Jul 17, 2025 18:33:33
Total Impressions: 6653

Machine Profile

Xerox Asset Tag:
Customer Asset Tag:
Service Phone Number:
Customer Support Number:
Supplies Phone Number:
System Administrator: Not set
Machine Location: machine location not set
Managed By
Primary MB Server:

Machine Hardware

Foreign Interface Card: not present
Device RAM Size: 1984 MB
Device Storage Size: used=2731MB/total=0MB (eMMC)
EPC Memory Size: 187 MB
Productivity Kit: used=101MB/total=0MB (HDD)
Finisher Type: Simple Catch Tray
Finisher Punch: None
Finisher Folder: not present

General Setup

Remote Services: Enabled
Remote Software Download: Enabled
Remote Services Trans. Time: 17:27
Xerox Workplace Cloud: Enabled
E-mail Alerts: Disabled
Service Plan: Sold
Geographic Region: unknown
GMT Offset: +05:30
Cloning Installation: Allowed (Encrypted Files Only)
File Sharing: Enabled
JBIG2: Lossless

Energy Saver

Deep Sleep: Enabled
Energy Saver Mode: Job Activated

Smart Proximity Sensor

Wake on Arrival:
Sleep on Departure:

Software Versions

Device Software: 123.027.005.24410
Patch Version: None
Network Controller: 123.027.24410
UI Panel Firmware: 6.2
Marking Engine: 237.002
Finisher: 000.000.000
Machine Upgrades: Allowed
Last Successful Upgrade: September 9, 2025 16:04:26

Media Trays

Tray 1: Plain, White and A4 (210 x 297 mm)
Bypass Tray: Plain, White and A4 (210 x 297 mm)

Installed Options

PS: Installed

Connectivity

Mobile Workflows

AirPrint Printing: Enabled
Mopria Printing: Enabled

Physical Connections

USB Settings
USB Type A Ports: All Enabled
USB Type B Port: Enabled

Wired:

Ethernet MAC Address: 9c:93:4e:fe:f6:79
Ethernet Speed/Duplex Setting: auto
Disabled

Wireless:

Wireless MAC Address:
Network Name (SSID):
BSSID:
Security Mode:
Encryption Algorithm:
Status:

Wi-Fi Direct:

Wireless Hardware: Enabled
Not Installed

Wi-Fi Protected Setup™ (WPS) Name:
Access Point (SSID):
Show Password on Device Touch Screen:

NFC:

iBeacon (Bluetooth®) for AirPrint Di... Enabled
iBeacon Hardware: Not Installed
Bluetooth Device Address:
iBeacon IP Address:

Protocols

TCP/IPv4:

IPv4 Address: 10.61.16.207
Subnet Mask: 255.255.255.0
Router/Gateway: 10.61.16.1
Automatic Addressing: DHCP
DHCP Server: DHCP
DHCP Lease Expiration:
BOOTP Broadcast: Disabled
Self Assigned Address State: Enabled
Self Assigned Address:

TCP/IPv6:

Link Local Address:
Use Router Supplied Prefix:
Stateless Global Address 1:
Stateless Global Address 2:
Manual Address:
DHCP Addressing: Disabled
DHCP Address:
Default Gateway:
DUID (DHCP Unique Identifier):

DNS Settings:

Requested Host Name: XRX9C934EFEF679
Verified Host Name:
Requested Domain Name:
Verified Domain Name:
Multicast DNS: Enabled
Release DHCP Leases and DNS Registrati... Disabled
Primary DNS Server: 10.61.7.16
Prefer IPv6 DNS over IPv4: Enabled

Bonjour:

Bonjour Printer Name: Xerox VersaLink B620 Printer (FE:F6:79)

HTTP:

Force Traffic over Secure Connection (H... Yes
IPP: Enabled

SNMP

SNMP v1/v2: Enabled
SNMP v3: Disabled

LPR/LPD:

Raw IP Printing: Enabled

LDAP

LDAP Server 1 Primary LDAP Address: 0.0.0.389
LDAP Server 1 Search Directory Root:
LDAP Server 1 Secure Connection (LDA... Disabled
LDAP Server 1 Validate Server Certificate... Disabled

SMTP

SMTP Server: 0.0.0.25
Connect Encryption (TLS): No Encryption
Validate Server Certificate (TLS):

Protocols (cont.)

POP3	
POP3 Server:	0.0.0.0:110
POP3 Secure Connection (TLS):	Disabled
POP3 Validate Server Certificate:	
E-mail Address:	
NTP:	Disabled
FTP Client:	Enabled
FTP Client Mode:	Passive
Web Services on Device:	Enabled

Apps**Printing**

Banner Sheet:	Enabled
Error Sheets:	Enabled
Paper Substitution:	Disabled
Tray Priority:	1,5
Archival Marking Mode	Off
PostScript	Installed
Level:	3
Version:	3021.101
PCL	
Version:	6
Font Name:	Courier
Custom Color Tables	Enabled
Label:	Not Installed
Print From:	Enabled
Saved Jobs for Reprint:	Enabled
Print From USB:	Enabled
Cloud Services:	Disabled

Accounting

Accounting Mode:	None
Network Accounting:	Disabled

Security**Authentication Configuration**

Machine UI Authentication:	Locally on the Device
Home:	Unlocked
Jobs Pathway:	Unlocked
Printer Pathway:	Unlocked
Device Website Authentication:	Locally on the Device
Authorization:	Locally on the Device

Authentication Server:

Kerberos

Xerox Secure Access:

Disabled

Audit Log:

Enabled

IP Sec:

Disabled

IP Filtering:

Disabled

Security Certificates

Machine Certificate:	Signed
Root Certificates Installed:	54

802.1x:

Disabled

Image Overwrite

Immediate:	Installed/Enabled
Scheduled:	Disabled

FIPS 140-3:

Disabled

TLS:

TLS 1.2 and TLS 1.3

TLS Hash: SHA-1, SHA-256 and above

Trellix Embedded Control:

Enhanced Security

Common User Data

Machine Name: Xerox VersaLink B620 Printer (FE:F6:79)
 IPv4 Address: 10.61.16.207
 Machine Serial Number: 5320705462
 Machine URL: https://10.61.16.207
 Machine Activation Date: Jul 17, 2025 18:33:33
 Total Impressions: 6655

Machine Profile

Xerox Asset Tag:
 Customer Asset Tag:
 Service Phone Number:
 Customer Support Number:
 Supplies Phone Number:
 System Administrator: Not set
 Machine Location: machine location not set

Managed By

Primary MB Server:

Machine Hardware

Foreign Interface Card: not present
 Device RAM Size: 1984 MB
 Device Storage Size: used=2731MB/total=0MB (eMMC)
 EPC Memory Size: 187 MB
 Productivity Kit: used=101MB/total=0MB (HDD)
 Finisher Type: Simple Catch Tray
 Finisher Punch: None
 Finisher Folder: not present

General Setup

Remote Services: Enabled
 Remote Software Download: Enabled
 Remote Services Trans. Time: 17:27
 Xerox Workplace Cloud: Enabled
 E-mail Alerts: Disabled
 Service Plan: Sold
 Geographic Region: unknown
 Startup Config Report: Enabled
 GMT Offset: +05:30
 Cloning Installation: Allowed (Encrypted Files Only)
 Allow Print Submission of Clone Files: Enabled
 File Sharing: Enabled
 iBIG2: Lossless

Energy Saver

Deep Sleep: Enabled
 Energy Saver Mode: Job Activated
 Sleep Mode Timer: 120 minutes
 Auto-Off: Disabled

Software Versions

Device Software: 123.027.005.24410
 Patch Version: None
 Network Controller: 123.027.24410
 UI Panel Firmware: 6.2
 User Interface: 123.027.24410
 Marking Engine: 237.002
 Finisher: 000.000.000
 OS: 237.002
 Software Upgrade: 005.016
 ALTBOOT Software Upgrade: 005.016

Machine Upgrades:

Allowed
 Last Successful Upgrade: September 9, 2025 16:04:26
 Scheduled Auto Upgrades: Disabled
 Auto Upgrade Start Time: Daily
 Auto Upgrade Server: 0.0.0.21

Media Trays

Tray 1: Plain, White and A4 (210 x 297 mm)
 Bypass Tray: Plain, White and A4 (210 x 297 mm)

Connectivity

Mobile Workflows

AirPrint Printing: Enabled
 Mopria Printing: Enabled
 Universal Print: Disabled
 Universal Print Registration Status: Not Registered

Physical Connections

USB Settings

USB Type A Ports: All Enabled
 USB Type B Port: Enabled
 Connection Timeout: 5 seconds

Wired:

Ethernet MAC Address: Enabled
 Ethernet Speed/Duplex Setting: 9c:93:4e:fe:f6:79
 auto

Wireless:

Wireless MAC Address: Disabled
 Network Name (SSID):
 BSSID:
 Security Mode:
 Encryption Algorithm:
 Status:

Wi-Fi Direct:

Wireless Hardware: Enabled
 Wi-Fi Protected Setup™ (WPS) Name: Not Installed

Connection Method:
 Subnet Prefix Address:
 Access Point (SSID):
 Show Password on Device Touch Screen:

NFC:

iBeacon (Bluetooth®) for AirPrint Di...: Enabled
 iBeacon Hardware: Enabled
 Bluetooth Device Address: Not Installed
 iBeacon IP Address:

Protocols

TCP/IPv4:

Enabled
 IPv4 Address: 10.61.16.207
 Subnet Mask: 255.255.255.0
 Router/Gateway: 10.61.16.1
 Automatic Addressing: DHCP

DHCP Server:
 DHCP Lease Expiration:
 BOOTP Broadcast:

Disabled

Self Assigned Address State:
 Self Assigned Address:

Enabled

TCP/IPv6:

Disabled
 Link Local Address:
 Use Router Supplied Prefix:
 Stateless Global Address 1:
 Stateless Global Address 2:
 Manual Address:
 DHCP Addressing:
 DHCP Address:
 Default Gateway:
 DUID (DHCP Unique Identifier):

DNS Settings:

Requested Host Name: XRX9C934EFEF679
 Verified Host Name:
 Requested Domain Name:
 Verified Domain Name:
 Multicast DNS: Enabled
 Release DHCP Leases and DNS Registrati...: Disabled
 Primary DNS Server: 10.61.7.16
 Alternate DNS Server 1: 10.61.10.6
 Alternate DNS Server 2: 10.61.7.15
 DNS Connection Timeout: 5
 Append Device Domain: Enabled
 Append Parent Domains: Disabled
 DNS Domain Search List: XEROXQA.COM
 Prefer IPv6 DNS over IPv4: Enabled

Installed Options

PS: Installed

Protocols (cont.)

Bonjour:
 Bonjour Printer Name: Xerox VersaLink B620 Printer (FE:F6:79)
HTTP:
 Port Number: 80
 Force Traffic over Secure Connection (H...): Yes
 Secure HTTP Port Number: 443
 Proxy Server: Disabled
 Proxy Server Address: 0.0.0.0:8080
 IPP: Enabled
 Secure IPP Mode: IPP and Secure IPPS
 IPP Network Path: http://10.61.16.207:631

SNMP
 SNMP v1/v2: Enabled
 SNMP v3: Disabled

LPR/LPD:
 Port Number: Enabled
 PDL Switching: 515
 PDL Banner Override: Disabled

Raw IP Printing:
 Port Number 1: Enabled
 Bidirectional: 9100
 End of Job Timeout: Disabled
 PDL Switching: 300

LDAP
 LDAP Server 1 Friendly Name:
 LDAP Server 1 Primary LDAP Address: 0.0.0.0:389
 LDAP Server 1 Alternate LDAP Address: 0.0.0.0:389
 LDAP Server 1 Search Directory Root:
 LDAP Server 1 Secure Connection (LDA...): Disabled
 LDAP Server 1 Validate Server Certificate...: Disabled

SMTP
 SMTP Server: 0.0.0.0:25
 Connect Encryption (TLS): No Encryption
 Validate Server Certificate (TLS):
 Max Message Size (KB): 10240
 Number of Fragments: 1
 Total Job Size (KB): 300000
 Job Splitting Boundary: Page Boundary
 Credentials for Auto E-mails: None
 SMTP Authentication Type: Basic Auth with SMTP

POP3
 POP3 Server: 0.0.0.0:110
 POP3 Secure Connection (TLS): Disabled
 E-mail Address:
 POP3 Validate Server Certificate:
 Receipt of E-mail via POP3: Disabled
 Send Confirm on Request: Enabled
 Incoming E-mail cover sheet: Enabled

NTP:
 Primary Server: [2403:0:22b:4:7006:5a52:f43b:a95f]:123
 Alternate Server: [::]:123

SLP:
 SLP: Disabled

FTP Client:
 FTP Client Mode: Enabled
 FTP Client Mode: Passive

Web Services on Device:
 WS-Discovery: Enabled
 WS-Discovery Multicast: Enabled
 WS-Print: Enabled

Web Services
 Digital Certificate Management and Securi...: Enabled
 Extensible Service Registration: Enabled
 Job Limits: Enabled
 Job Management Extension: Enabled
 Device Configuration: Enabled
 Session Data: Enabled
 User Interface Configuration: Enabled
 EIP Proxy Configuration: Enabled
 Xerox Secure Access: Disabled
 EIP SNMP Configuration: Enabled
 Print Submission: Enabled
 Mass Storage Access: Enabled
 Card Reader Access: Enabled
 Authentication & Accounting Configur...: Enabled
 Export Audit Log: Enabled
 Trellix Embedded Control: Enabled

Apps

Printing
 Banner Sheet: Enabled
 Sys/Start Job: Disabled
 Delete Held Jobs After: 3 Day(s) 0 Hour(s) 0 Minute(s)
 Error Sheets: Enabled
 Paper Substitution: Disabled
 Tray Priority: 1,5
 Default Copies: 1
 Default Job Type: Normal Print
 Default Paper Size: x=210mm, y=297mm
 Default Paper Color: White
 Default 2 Sided Printing: 2 Sided
 Default Output Tray: Center Tray
 Default Output Color: Black & White
 Default Collated Sets: Enabled
 Default Stapling: Not Available
 Offsetting Between Jobs: No Offset Between Jobs
 Archival Marking Mode: Off
PostScript
 Level: Installed
 Version: 3
 Image Quality: 3021.101 Enhanced

PCL
 Version: 6
 Pitch Size: 10.00
 Point Size: 12.00
 Font Name: Courier
 Lines Per Page: 64

Custom Color Tables
 Label: Enabled
 Label: Not Installed

Print From:
 Saved Jobs for Reprint: Enabled
 Print From USB: Enabled
 Cloud Services: Disabled

Accounting

Accounting Mode: None
 Network Accounting: Disabled

Security

Authentication Configuration

Machine UI Authentication: Locally on the Device
 Home: Unlocked
 Jobs Pathway: Unlocked
 Printer Pathway: Unlocked
 Device Website Authentication: Locally on the Device
 Authorization: Locally on the Device

Authentication Server:

Kerberos Primary Realm:
 Kerberos Primary Address: 0.0.0.88
 Kerberos Alt 1 Realm:
 Kerberos Alt 1 Address: 0.0.0.88
 SMB NT Domain:
 SMB Alt 1 NT Domain:
 SmartCard Ctrl Server: 0.0.0.443
 SmartCard Ctrl Domain:
 SmartCard GCSP URL:
 Card Reader Upgrade Policy: Enabled
 Card Reader Firmware Version:

Xerox Secure Access:

Secure Access Server: Disabled
 Secure Access Path: 0.0.0.443

Audit Log:

Enabled

IP Sec:

Disabled

IP Filtering:

Disabled

Security Certificates

Machine Certificate: Signed

Root Certificates Installed: 54

802.1x: Disabled

Image Overwrite

Immediate: Installed/Enabled

Scheduled: Disabled

Scheduled Frequency:

FIPS 140-3: Disabled

TLS: TLS 1.2 and TLS 1.3

TLS Hash: SHA-1, SHA-256 and above

Trellix Embedded Control: Enhanced Security

Extensible Service Setup

Third Generation Browser: X3G_3.24.23_2405_012_01.00.00

Widget Version: v1.3.17 e8 20140613

Widget Version: v2.5.04 g9 20240123