

## Xerox® VersaLink® B415 MFP

## Configuration Report

Printed at 14 Oct, 2025 01:02 AM

xerox™

## Common User Data

Machine Name: Xerox VersaLink B415 MFP (DC.B8:44)  
IPv4 Address: 10.61.16.69  
Machine Serial Number: 5330005345  
Fax Line 1:  
Machine URL: https://10.61.16.69  
Machine Activation Date: Jul 10, 2025 18:17:28  
Total Impressions: 9654

## Machine Profile

Xerox Asset Tag:  
Customer Asset Tag:  
Service Phone Number:  
Customer Support Number:  
Supplies Phone Number:  
Recycling Phone Number:  
System Administrator: Not set  
Machine Location: machine location not set

## Managed By

Primary MB Server:

## Machine Hardware

Fax Card: Not Present  
Fax Memory Size: 0 MB  
Foreign Interface Card: not present  
Device RAM Size: 1984 MB  
Device Storage Size: used: 2752MB/total: 14004MB (eMMC)  
EPC Memory Size: 187 MB  
Productivity Kit: Not Installed  
Finisher Type: Simple Catch Tray  
Finisher Punch: None  
Finisher Folder: not present  
Multi-feed Detection Kit: Not Installed

## General Setup

Remote Services: Enabled  
Remote Software Download: Enabled  
Remote Services Trans. Time: 22:25  
Xerox Workplace Cloud: Enabled  
E-mail Alerts: Disabled  
Service Plan: Metered  
Geographic Region: unknown  
GMT Offset: +05:30  
Cloning Installation: Allowed (Encrypted Files Only)  
File Sharing: Enabled  
JBIG2: Lossless

## Energy Saver

Deep Sleep: Disabled  
Energy Saver Mode: Job Activated

## Smart Proximity Sensor

Wake on Arrival: Not Available  
Sleep on Departure:

## Software Versions

Device Software: 123.029.005.28100  
Patch Version: None  
Network Controller: 123.029.28100  
UI Panel Firmware: 6.2  
Marking Engine: 237.004  
Document Feeder: 237.004  
Finisher: 000.000.000  
Fax: 000.000.000  
Scanner: 237.004

## Machine Upgrades:

Last Successful Upgrade: Allowed  
October 13, 2025 19:15:42

## Media Trays

Tray 1: Plain, White and A4 (210 x 297 mm)  
Tray 2: Plain, White and Letter (8.5 x 11")  
Tray 3: Plain, White and Letter (8.5 x 11")  
Tray 4: Plain, White and Letter (8.5 x 11")  
Bypass Tray: Plain, White and A4 (210 x 297 mm)

## Installed Options

PS: Installed

## Connectivity

## Mobile Workflows

AirPrint Printing: Enabled  
Mopria Printing: Enabled  
AirPrint / Mopria Scanning: Enabled  
Authentication Required: Disabled

## Physical Connections

## USB Settings

USB Type A Ports: Front Only Disabled  
USB Type B Port: Disabled

## Wired:

Ethernet MAC Address: 78:8c:77:dc:b8:44  
Ethernet Speed/Duplex Setting: auto  
Disabled

## Wireless:

Wireless MAC Address:

Network Name (SSID):

BSSID:

Security Mode:

Encryption Algorithm:

Status:

## Wi-Fi Direct:

Wireless Hardware: Enabled  
Wi-Fi Protected Setup™ (WPS) Name: Not Installed

Access Point (SSID):

Show Password on Device Touch Screen:

## NFC:

iBeacon (Bluetooth®) for AirPrint DL...

iBeacon Hardware:

Bluetooth Device Address:

iBeacon IP Address:

## Protocols

## TCP/IPv4:

IPv4 Address: Enabled  
10.61.16.69  
Subnet Mask: 255.255.255.0  
Router/Gateway: 10.61.16.1  
Automatic Addressing: DHCP  
DHCP Server:  
DHCP Lease Expiration:  
BOOTP Broadcast: Disabled  
Self Assigned Address State: Enabled  
Self Assigned Address:

## TCP/IPv6:

Link Local Address: Disabled  
Use Router Supplied Prefix:  
Stateless Global Address 1:  
Stateless Global Address 2:  
Manual Address:  
DHCP Addressing:  
DHCP Address:  
Default Gateway:  
DUID (DHCP Unique Identifier):

## DNS Settings:

Requested Host Name: XR788C77DC8844  
Verified Host Name:  
Requested Domain Name:  
Verified Domain Name:  
Multicast DNS: Enabled  
Release DHCP Leases and DNS Registrati...: Disabled  
Primary DNS Server: 10.61.7.16  
Prefer IPv6 DNS over IPv4: Enabled

## Bonjour:

Bonjour Printer Name: Xerox VersaLink B415 MFP (DC.B8:44)  
HTTP: Enabled  
Force Traffic over Secure Connection (H...: Yes  
IPP: Enabled

## SNMP

SNMP v1/v2: Enabled  
SNMP v3: Disabled

## LPR/LPD:

Enabled

## Raw IP Printing:

Enabled

## LDAP

LDAP Server 1 Primary LDAP Address: 0.0.0.0:389

LDAP Server 1 Search Directory Root:

LDAP Server 1 Secure Connection (LD...:

LDAP Server 1 Validate Server Certificate...

## SMTP

SMTP Server: 0.0.0.0:25  
Connect Encryption (TLS): No Encrypt  
Validate Server Certificate (TLS):  
SMTP Authentication Type: Basic Auth with SMTP

otocols (cont.)

POP3 Server: 0.0.0.0:110  
POP3 Secure Connection (TLS): Disabled  
POP3 Validate Server Certificate:  
E-mail Address: Disabled  
NTP: Enabled  
FTP Client: Passive  
FTP Client Mode: Passive  
Web Services on Device: Enabled

ps

rinting Enabled  
Banner Sheet: Enabled  
Error Sheets: Enabled  
Paper Substitution: 1,2,3,4,5  
Tray Priority: Off  
Archival Marking Mode Installed  
PostScript Level: 3  
Version: 3021 101  
PCL Version: 6  
Font Name: Courier  
Custom Color Tables Enabled  
Label: Not Installed  
Fax: Not Present

Fax Line1:  
Fax Line2:  
Server Fax: Enabled  
Repository Protocol: SMB  
Repository Server: 0.0.0.0:0

Repository Document Path: Enabled  
Workflow Scanning: Enabled

Email: Disabled  
Scan to Mailbox: 672 MB  
Storage Capacity (MB): 49 MB  
Storage Used (MB): Enabled  
Cleanup of Public Folders: Enabled  
Cleanup of Created Folders: Daily  
Cleanup Time: Disabled

Scan to Home: Enabled  
Scan To: Disabled  
Cloud Services: Enabled  
Print From: Enabled  
Saved Jobs for Reprint: Enabled  
Print From USB: Disabled  
Print from MailBox: Disabled  
Cloud Services: Disabled

Accounting

Accounting Mode: None  
Network Accounting: Disabled

Security

Authentication Configuration

Machine UI Authentication: Locally on the Device  
Home: Unlocked  
Jobs: Unlocked  
Device: Unlocked  
Device Website Authentication: Locally on the Device  
Authorization: Locally on the Device  
Retrieve E-mail from LDAP: Enabled  
Authentication Server: Kerberos  
Xerox Secure Access: Disabled  
Audit Log: Enabled  
IP Set: Disabled  
IP Filtering: Disabled

Security Certificates

Machine Certificate: Signed  
Root Certificates Installed: 48  
802.1x: Disabled

Job Data Removal: Disabled  
Scheduled: Disabled

FIPS 140-3: TLS 1.2 and TLS 1.3  
TLS: SHA-1, SHA-256 and above  
TLS Hash: Enhanced Security

Trellix Embedded Control:

## Common User Data

Machine Name: Xerox VersaLink B415 MFP (DC:88:44)  
IPv4 Address: 10.61.16.69  
Machine Serial Number: 5330005345  
Fax Line1:  
Machine URL: https://10.61.16.69  
Machine Activation Date: Jul 10, 2025 18:17:28  
Total Impressions: 9654

## Machine Profile

Xerox Asset Tag:  
Customer Asset Tag:  
Service Phone Number:  
Customer Support Number:  
Supplies Phone Number:  
Recycling Phone Number:  
System Administrator:  
Machine Location:  
Managed By  
Primary MIB Server:

## Machine Hardware

Fax Card: Not Present  
Fax Memory Size: 0 MB  
Foreign Interface Card: not present  
Device RAM Size: 1984 MB  
Device Storage Size: used=2752MB/total=14004MB (eMMC)  
EPC Memory Size: 187 MB  
Productivity Kit: Not Installed  
Finisher Type: Simple Catch Tray  
Finisher Punch: None  
Finisher Folder: not present  
Multi-feed Detection Kit: Not Installed

## General Setup

Remote Services: Enabled  
Remote Software Download: Enabled  
Remote Services Trans. Time: 22:25  
Xerox Workplace Cloud: Enabled  
E-mail Alerts: Disabled  
Service Plan: Metered  
Geographic Region: unknown  
Startup Config Report: Enabled  
GMT Offset: +05:30  
Cloning Installation: Allowed (Encrypted Files Only)  
Allow Print Submission of Clone Files: Enabled  
File Sharing: Enabled  
JBIG2: Lossless

## Energy Saver

Deep Sleep: Disabled  
Energy Saver Mode: Job Activated  
Sleep Mode Timer: 120 minutes  
Auto-Off: Disabled

## Software Versions

Device Software: 123.029.005.28100  
Patch Version: None  
Network Controller: 123.029.28100  
UI Panel Firmware: 6.2  
User Interface: 123.029.28100  
Marking Engine: 237.004  
Copy Controller: 123.029.28100  
Document Feeder: 237.004  
Finisher: 000.000.000  
Fax: 000.000.000  
OS: 237.004  
Scanner: 237.004  
Software Upgrade: 006.001  
AT/BOOT Software Upgrade: 006.001  
Tray 2: A19.1\_B3.1  
Tray 3: A19.1\_B3.1  
Tray 4: A19.1\_B3.1

## Machine Upgrades

Last Successful Upgrade: Allowed  
Scheduled Auto Upgrades: October 13, 2025 19:15:42  
Auto Upgrade Start Time: Disabled  
Auto Upgrade Server: Daily  
0.0.0.0:21

## Media Trays

Tray 1: Plain, White and A4 (210 x 297 mm)  
Tray 2: Plain, White and Letter (8.5 x 11")  
Tray 3: Plain, White and Letter (8.5 x 11")  
Tray 4: Plain, White and Letter (8.5 x 11")  
Bypass Tray: Plain, White and A4 (210 x 297 mm)

## Connectivity

## Mobile Workflows

AirPrint Printing: Enabled  
Mopria Printing: Enabled  
AirPrint / Mopria Scanning: Enabled  
Authentication Required: Disabled  
Universal Print: Disabled  
Universal Print Registration Status: Not Registered

## Physical Connections

## USB Settings

USB Type A Ports: Front Only Disabled  
USB Type B Port: Disabled  
Wired: Enabled  
Ethernet MAC Address: 78:8c:77:dc:b8:44  
Ethernet Speed/Duplex Setting: auto  
Wireless: Disabled

Wireless MAC Address:  
Network Name (SSID):  
BSSID:  
Security Mode:  
Encryption Algorithm:  
Status:

## Wi-Fi Direct:

Wireless Hardware: Enabled  
Wi-Fi Protected Setup™ (WPS) Name: Not Installed  
Connection Method:  
Subnet Prefix Address:  
Access Point (SSID):  
Show Password on Device Touch Screen:

## NFC:

iBeacon (Bluetooth®) for AirPrint Di... Disabled  
iBeacon Hardware: Enabled  
Bluetooth Device Address: Not Installed  
iBeacon IP Address:

## Protocols

## TCP/IPV4:

IPv4 Address: Enabled  
Subnet Mask: 10.61.16.69  
Router/Gateway: 255.255.255.0  
Automatic Addressing: 10.61.16.1  
DHCP Server: DHCP

DHCP Lease Expiration:  
BOOTP Broadcast: Disabled  
Self Assigned Address State: Enabled  
Self Assigned Address:

## TCP/IPV6:

Link Local Address:  
Use Router Supplied Prefix:  
Stateless Global Address 1:  
Stateless Global Address 2:  
Manual Address:  
DHCP Addressing:  
DHCP Address:  
Default Gateway:  
DUID (DHCP Unique Identifier):

## DNS Settings:

Requested Host Name: XR788C77DC8844  
Verified Host Name:  
Requested Domain Name:  
Verified Domain Name:  
Multicast DNS: Enabled  
Release DHCP Leases and DNS Registrati... Disabled  
Primary DNS Server: 10.61.7.16  
Alternate DNS Server 1: 10.61.10.6  
Alternate DNS Server 2: 10.61.7.15  
DNS Connection Timeout: 5  
Append Device Domain: Enabled  
Append Parent Domains: Disabled  
DNS Domain Search List: XEROXQA.COM.  
Prefer IPv6 DNS over IPv4: Enabled

## Installed Options

PS: Installed

## Protocols (cont.)

**Bonjour**  
 Bonjour Printer Name: Xerox VersaLink B415 MFP (DC:88:44)  
 HTTP:  
 Port Number: 80  
 Force Traffic over Secure Connection (H...): Yes  
 Secure HTTP Port Number: 443  
 Proxy Server: Automatic  
 Proxy Server Address: 0.0.0.0:8080  
 IPP:  
 Secure IPP Mode: Enabled  
 IPP Network Path: http://10.61.16.69:631

**SNMP**  
 SNMP v1/v2: Enabled  
 SNMP v3: Disabled  
 LPR/LPD:  
 Port Number: 515  
 PDL Switching: Disabled  
 PDL Banner Override: Disabled  
 Raw IP Printing:  
 Port Number 1: 9100  
 Bidirectional: Disabled  
 End of Job Timeout: 300  
 PDL Switching: Disabled

**LDAP**  
 LDAP Server 1 Friendly Name:  
 LDAP Server 1 Primary LDAP Address: 0.0.0.0:389  
 LDAP Server 1 Alternate LDAP Address: 0.0.0.0:389  
 LDAP Server 1 Search Directory Root:  
 LDAP Server 1 Secure Connection (LDA...): Disabled  
 LDAP Server 1 Validate Server Certificate...: Disabled

**SMTP**  
 SMTP Server: 0.0.0.0:25  
 Connect Encryption (TLS): No Encryption  
 Validate Server Certificate (TLS):  
 Max Message Size (KB): 10240  
 Number of Fragments: 1  
 Total Job Size (KB): 300000  
 Job Splitting Boundary: Page Boundary  
 Credentials for Auto E-mails: None  
 Credentials for Walkup User: None  
 SMTP Authentication Type: Basic Auth with SMTP

**POP3**  
 POP3 Server: 0.0.0.0:110  
 POP3 Secure Connection (TLS): Disabled  
 E-mail Address:  
 POP3 Validate Server Certificate: Disabled  
 Receipt of E-mail via POP3: Enabled  
 Send Confirm on Request: Enabled  
 Incoming E-mail cover sheet: Disabled

**NTS**  
 Primary Server: [2403:0:22b:4:a14d:38b3:33b:477a]:123  
 Alternate Server: [2403:0:22b:4:39f0:35cde8a8:3087]:123

**SLP**  
 Enabled

**FTP Client**  
 FTP Client Mode: Passive

**Web Services on Device**  
 WS-Discovery: Enabled  
 WS-Discovery Multicast: Enabled  
 WS-Print: Enabled  
 WS-Scan: Enabled

**Web Services**  
 Copy Submission: Enabled  
 Digital Certificate Management and Secur...: Enabled  
 Extensible Service Registration: Enabled  
 Job Limits: Enabled  
 Job Management Extension: Enabled  
 Device Configuration: Enabled  
 Scan Submission: Enabled  
 Scan Workflow Management: Enabled  
 Session Data: Enabled  
 User Interface Configuration: Enabled  
 EIP Proxy Configuration: Enabled  
 Xerox Secure Access: Disabled  
 EIP SNMP Configuration: Enabled  
 Print Submission: Enabled  
 Scan Template Mgmt: Enabled  
 Mass Storage Access: Enabled  
 Card Reader Access: Enabled  
 Authentication & Accounting Configur...: Enabled  
 Export Audit Log: Enabled  
 Trellix Embedded Control: Enabled

## Apps

## Printing

Banner Sheet: Enabled  
 Sys/Start Job: Disabled  
 Delete Held Jobs After: 3 Day(s) 0 Hour(s) 0 Minute(s)  
 Error Sheets: Enabled  
 Paper Substitution: Enabled  
 Tray Priority: 1,2,3,4,5  
 Default Copies: 1  
 Default Job Type: Normal Print  
 Default Paper Size: x=8.50 inches, y=11.00 inches  
 Default Paper Color: White  
 Default 2 Sided Printing: 2 Sided  
 Default Output Tray: Center Tray  
 Default Output Color: Black & White  
 Default Collated Sets: Enabled  
 Default Stapling: Not Available  
 Offsetting Between Jobs: No Offset Between Jobs  
 Archival Marking Mode: Off  
 PostScript:  
 Level: Installed  
 Version: 3  
 Image Quality: 3021 101 Enhanced

**PCL**  
 Version: 6  
 Pitch Size: 10.00  
 Point Size: 12.00  
 Font Name: Courier  
 Lines Per Page: 60  
 Custom Color Tables: Enabled  
 Label: Not Installed  
 Not Present

## Fax:

Fax Line1:

Fax Line2:

## Server Fax:

Confirmation Sheet:

Delay Start:

Repository Protocol:

Repository Server:

Repository Document Path:

## Workflow Scanning:

Confirmation Sheet:

Default Repository Protocol:

Default Repository Server:

Default Repository Document Path:

Default Repository Login Credentials:

Alt1 Repository Protocol:

Alt1 Repository Server:

Alt1 Repository Document Path:

Alt1 Repository Login Credentials:

Workflow Pool Protocol:

Workflow Pool Server:

Workflow Pool Path:

## Email:

Default From Address:

Confirmation Sheet:

Auto Send to Self:

E-mail Security:

## Scan to Mailbox:

View Mailboxes by Default:

Storage Capacity (MB):

Storage Used (MB):

Cleanup of Public Folders:

Cleanup of Created Folders:

Cleanup Time:

## Scan to Home:

Friendly Name:

Workflow Name:

Auto Create Subdir:

Append User Name to Path:

Auto Create User Name Dir:

## Scan To:

Cloud Services:

## Print From:

Saved Jobs for Reprint:

Print From USB:

Print From MailBox:

Cloud Services:

Enabled  
 Disabled  
 3 Day(s) 0 Hour(s) 0 Minute(s)  
 Enabled  
 Enabled  
 1,2,3,4,5  
 1  
 Normal Print  
 x=8.50 inches, y=11.00 inches  
 White  
 2 Sided  
 Center Tray  
 Black & White  
 Enabled  
 Not Available  
 No Offset Between Jobs  
 Off  
 Installed  
 3  
 3021 101  
 Enhanced

6  
 10.00  
 12.00  
 Courier  
 60  
 Enabled  
 Not Installed  
 Not Present

Enabled  
 Errors Only  
 Disabled  
 SMB  
 0.0.0.0:0

Enabled  
 Errors Only  
 SMB  
 0.0.0.0:0

Device  
 SMB  
 0.0.0.0:0

Device  
 SMB  
 0.0.0.0:0

Enabled

Errors Only  
 Disabled  
 Disabled  
 Disabled  
 Enabled  
 672 MB  
 49 MB  
 Enabled  
 Enabled  
 Daily  
 Disabled

Disabled  
 Disabled  
 Disabled  
 Disabled  
 Enabled  
 Disabled  
 Disabled

Disabled  
 Enabled  
 Enabled  
 Enabled  
 Disabled

**Accounting**

Accounting Mode: None  
Network Accounting: Disabled

**Security****Authentication Configuration**

Machine UI Authentication: Locally on the Device  
Home: Unlocked  
Jobs: Unlocked  
Device: Unlocked  
Device Website Authentication: Locally on the Device  
Authorization: Locally on the Device  
Retrieve E-mail from LDAP: Enabled

**Authentication Server:**

Kerberos: Kerberos  
Kerberos Primary Realm: 0.0.0.0:88  
Kerberos Primary Address: 0.0.0.0:88  
Kerberos Alt 1 Realm: 0.0.0.0:88  
Kerberos Alt 1 Address: 0.0.0.0:88  
SMB NT Domain: 0.0.0.0:443  
SMB Alt 1 NT Domain: 0.0.0.0:443  
SmartCard Ctrl Server: 0.0.0.0:443  
SmartCard Ctrl Domain: 0.0.0.0:443  
SmartCard OCSP URL: 0.0.0.0:443  
Card Reader Upgrade Policy: Enabled  
Card Reader Firmware Version: 0.0.0.0:443

**Xerox Secure Access:**

Secure Access Server: Disabled  
Secure Access Path: 0.0.0.0:443

**Audit Log:**

IP Sec: Disabled  
IP Filtering: Disabled

**Security Certificates**

Machine Certificate: Signed  
Root Certificates Installed: 48  
802.1x: Disabled

**Job Data Removal:**

Scheduled: Disabled  
Scheduled Frequency: 0.0.0.0:443

**FIPS 140-3:**

TLS: Disabled  
TLS Hash: TLS 1.2 and TLS 1.3  
SHA-1, SHA-256 and above

**Trellix Embedded Control:**

Enhanced Security

**Extensible Service Setup**

Third Generation Browser: X3G\_3.24.23\_2405\_012\_01.00.00  
Widget Version: v1.3.17 c8 20140613  
Widget Version: v2.5.04 g9 20240123

