

Common User Data

Machine Name: Xerox VersaLink C620 (FC:36:4B)  
IPv4 Address: 10.61.16.175  
Machine Serial Number: 5322980355  
Machine URL: http://10.61.16.175  
Machine Activation Date: Sep 10, 2025 21:46:30  
Black Impressions: 8060  
Color Impressions: 7971  
Total Impressions: 16031

Machine Profile

Xerox Asset Tag:  
Customer Asset Tag:  
Service Phone Number:  
Customer Support Number:  
Supplies Phone Number:  
Recycling Phone Number:  
System Administrator:  
Machine Location:  
Managed By  
Primary MB Server:

+191-4534-456  
Not set  
machine location not set

Machine Hardware

Foreign Interface Card: not present  
Device RAM Size: 1984 MB  
Device Storage Size: used=2945MB/total=14004MB (eMMC)  
EPC Memory Size: 187 MB  
Productivity Kit: Not Installed  
Finisher Type: Simple Catch Tray  
Finisher Punch: None  
Finisher Folder: not present

General Setup

Remote Services: Enabled  
Remote Software Download: Enabled  
Remote Services Trans. Time: 19:35  
Xerox Workplace Cloud: Enabled  
E-mail Alerts: Disabled  
Service Plan: Metered  
Geographic Region: unknown  
Startup Config Report: Enabled  
GMT Offset: +05:30  
Cloning Installation: Allowed (Encrypted Files Only)  
Allow Print Submission of Clone Files: Disabled  
File Sharing: Enabled  
JBG2: Lossless  
Energy Saver  
Deep Sleep: Disabled  
Energy Saver Mode: Job Activated  
Sleep Mode Timer: 120 minutes  
Auto-Off: Disabled

Software Versions

Device Software: 123.026.005.28800  
Patch Version: None  
Network Controller: 123.026.28800  
UI Panel Firmware: 6.2  
User Interface: 123.026.28800  
Marking Engine: 237.004  
Finisher: 000.000.000  
OS: 237.004  
Software Upgrade: 006.001  
ALTBOOT Software Upgrade: 006.001  
Machine Upgrades:  
Last Successful Upgrade: October 22, 2025 16:14:57  
Scheduled Auto Upgrades: Disabled  
Auto Upgrade Start Time: Daily  
Auto Upgrade Server: 0.0.0.0:21

Media Trays

Tray 1: Plain, White and A4 (210 x 297 mm)  
Bypass Tray: Plain, White and A4 (210 x 297 mm)

Connectivity

Mobile Workflows  
AirPrint Printing: Enabled  
Mopria Printing: Enabled  
Universal Print: Disabled  
Universal Print Registration Status: Not Registered  
Physical Connections  
USB Settings  
USB Type A Ports: All Enabled  
USB Type B Port: Enabled  
Connection Timeout: 5 seconds  
Wired: Enabled  
Ethernet MAC Address: 9c93:4e:fc:36:4b  
Ethernet Speed/Duplex Setting: auto  
Wireless: Disabled  
Wireless MAC Address:  
Network Name (SSID):  
BSSID:  
Security Mode:  
Encryption Algorithm:  
Status:  
Wi-Fi Direct: Enabled  
Wireless Hardware: Not Installed  
Wi-Fi Protected Setup™ (WPS) Name:  
Connection Method:  
Subnet Prefix Address:  
Access Point (SSID):  
Show Password on Device Touch Screen:  
NFC: Enabled  
iBeacon (Bluetooth®) for AirPrint Di...: Enabled  
iBeacon Hardware: Not Installed  
Bluetooth Device Address:  
iBeacon IP Address:

Protocols

TCP/IPv4: Enabled  
IPv4 Address: 10.61.16.175  
Subnet Mask: 255.255.255.0  
Router/Gateway: 10.61.16.1  
Automatic Addressing: DHCP  
DHCP Server:  
DHCP Lease Expiration:  
BOOTP Broadcast: Disabled  
Self Assigned Address State: Enabled  
Self Assigned Address:  
TCP/IPv6: Disabled  
Link Local Address:  
Use Router Supplied Prefix:  
Stateless Global Address 1:  
Stateless Global Address 2:  
Manual Address:  
DHCP Addressing:  
DHCP Address:  
Default Gateway:  
DUID (DHCP Unique Identifier):  
DNS Settings:  
Requested Host Name: XR9C934EFC364B  
Verified Host Name:  
Requested Domain Name:  
Verified Domain Name:  
Multicast DNS: Enabled  
Release DHCP Leases and DNS Registrati...: Disabled  
Primary DNS Server: 10.61.7.16  
Alternate DNS Server 1: 10.61.10.6  
Alternate DNS Server 2: 10.61.7.15  
DNS Connection Timeout: 5  
Append Device Domain: Enabled  
Append Parent Domains: Disabled  
DNS Domain Search List: XEROXQA.COM.  
Prefer IPv6 DNS over IPv4: Enabled

Installed Options

PS: Installed

## Protocols (cont.)

## Bonjour:

Bonjour Printer Name: Xerox VersaLink C620 (FC:36:4B)

## HTTP:

Port Number: 80  
Force Traffic over Secure Connection (H... No  
Secure HTTP Port Number: 443  
Proxy Server: Manual  
Proxy Server Address: 10.177.8.91:8080  
IPP Enabled  
Secure IPP Mode: IPP and Secure IPPS  
IPP Network Path: http://10.61.16.175:631

## SNMP

SNMP v1/v2: Enabled  
SNMP v3: Disabled

## LPR/LPD:

Port Number: 515  
PDL Switching: Disabled  
PDL Banner Override: Disabled

## Raw IP Printing:

Port Number 1: Enabled  
Bidirectional: Disabled  
End of Job Timeout: 300  
PDL Switching: Disabled

## LDAP

LDAP Server 1 Friendly Name:  
LDAP Server 1 Primary LDAP Address: 0.0.0.0:389  
LDAP Server 1 Alternate LDAP Address: 0.0.0.0:389  
LDAP Server 1 Search Directory Root:  
LDAP Server 1 Secure Connection (LDA... Disabled  
LDAP Server 1 Validate Server Certificate... Disabled

## SMTP

SMTP Server: 0.0.0.0:25  
Connect Encryption (TLS): No Encryption  
Validate Server Certificate (TLS):  
Max Message Size (KB): 10240  
Number of Fragments: 1  
Total Job Size (KB): 300000  
Job Splitting Boundary: Page Boundary  
Credentials for Auto E-mails: None  
SMTP Authentication Type: Basic Auth with SMTP

## POP3

POP3 Server: 0.0.0.0:110  
POP3 Secure Connection (TLS): Disabled

## POP3 Validate Server Certificate:

E-mail Address:  
Receipt of E-mail via POP3: Disabled  
Send Confirm on Request: Enabled  
Incoming E-mail cover sheet: Enabled

## NTP:

Primary Server: 0.0.0.0:123  
Alternate Server: 0.0.0.0:123

## SLP:

Disabled

## FTP Client:

Enabled

FTP Client Mode: Passive

## Web Services on Device:

Enabled

WS-Discovery: Enabled

WS-Discovery Multicast: Enabled

WS-Print: Enabled

## Web Services

Digital Certificate Management and Securi... Enabled

Extensible Service Registration: Enabled

Job Limits: Enabled

Job Management Extension: Enabled

Device Configuration: Enabled

Session Data: Enabled

User Interface Configuration: Enabled

EIP Proxy Configuration: Enabled

Xerox Secure Access: Disabled

EIP SNMP Configuration: Enabled

Print Submission: Enabled

Mass Storage Access: Enabled

Card Reader Access: Enabled

Authentication &amp; Accounting Configur... Enabled

Export Audit Log: Enabled

Trellix Embedded Control: Enabled

## Apps

## Printing

Banner Sheet: Disabled  
Sys/Start Job: Disabled  
Delete Held Jobs After: 3 Day(s) 0 Hour(s) 0 Minute(s)  
Error Sheets: Enabled  
Paper Substitution: Enabled  
Tray Priority: 1,6  
Default Copies: 1  
Default Job Type: Normal Print  
Default Paper Size: x=210mm, y=297mm  
Default Paper Color: White  
Default 2 Sided Printing: 2 Sided  
Default Output Tray: Center Tray  
Default Output Color: Color  
Default Collated Sets: Enabled  
Default Stapling: Not Available  
Offsetting Between Jobs: No Offset Between Jobs  
Archival Marking Mode: Off  
PostScript: Installed  
Level: 3  
Version: 3021.101  
Image Quality: Enhanced

## PCL

Version: 6  
Pitch Size: 10.00  
Point Size: 12.00  
Font Name: Courier  
Lines Per Page: 64  
Custom Color Tables: Enabled  
Label: Not Installed

## Print From:

Saved Jobs for Reprint: Enabled  
Print From USB: Enabled  
Cloud Services: Disabled

Accounting

Accounting Mode: None  
Network Accounting: Disabled

Security

Authentication Configuration

Machine UI Authentication: Locally on the Device  
Home: Unlocked  
Jobs Pathway: Unlocked  
Printer Pathway: Unlocked  
Device Website Authentication: Locally on the Device  
Authorization: Locally on the Device  
Kerberos

Authentication Server:

Kerberos Primary Realm:  
Kerberos Primary Address: 0.0.0.0:88  
Kerberos Alt 1 Realm:  
Kerberos Alt 1 Address: 0.0.0.0:88  
SMB NT Domain:  
SMB Alt 1 NT Domain:  
Smartcard Ctrl Server: 0.0.0.0:443  
Smartcard Ctrl Domain:  
SmartCard OCSP URL:  
Card Reader Upgrade Policy: Enabled  
Card Reader Firmware Version:

Xerox Secure Access:

Secure Access Server: Disabled  
Secure Access Path: 0.0.0.0:443

Audit Log:

IP Sec: Enabled  
IP Filtering: Disabled  
Disabled

Security Certificates

Machine Certificate: Signed  
Root Certificates Installed: S4  
802.1x: Disabled

Job Data Removal:

Scheduled: Disabled  
Scheduled Frequency:

FIPS 140-3:

TLS: Disabled  
TLS Hash: TLS 1.2 and TLS 1.3  
SHA-1, SHA-256 and above  
Trellix Embedded Control: Enhanced Security

Extensible Service Setup

Third Generation Browser: X3G\_3.24.23\_2.40.5\_012\_01.00.00  
Widget Version: v1.3.17 c8 20140613  
Widget Version: v2.5.04 g9 20240123



## Protocols (cont.)

POP3  
POP3 Server: 0.0.0.0:110  
POP3 Secure Connection (TLS): Disabled  
POP3 Validate Server Certificate:  
E-mail Address:  
NTP: Disabled  
FTP Client: Enabled  
FTP Client Mode: Passive  
Web Services on Device: Enabled

## Apps

## Printing

Banner Sheet: Disabled  
Error Sheets: Enabled  
Paper Substitution: Enabled  
Troy Priority: 1,6  
Archival Marking Mode: Off  
PostScript: Installed  
Level: 3  
Version: 3021.101  
PCL  
Version: 6  
Font Name: Courier  
Custom Color Tables: Enabled  
Label: Not Installed  
Print From: Enabled  
Saved Jobs for Reprint: Enabled  
Print From USB: Enabled  
Cloud Services: Disabled

## Accounting

Accounting Mode: None  
Network Accounting: Disabled

## Security

## Authentication Configuration

Machine UI Authentication: Locally on the Device  
Home: Unlocked  
Jobs Pathway: Unlocked  
Printer Pathway: Unlocked  
Device Website Authentication: Locally on the Device  
Authorization: Locally on the Device

## Authentication Server:

Xerox Secure Access: Disabled

## Audit Log:

IP Sec: Disabled

## IP Filtering:

Security Certificates: Disabled

Machine Certificate: Signed

Root Certificates Installed: 54

802.1x: Disabled

## Job Data Removal:

Scheduled: Disabled

FIPS 140-3: Disabled

TLS: TLS 1.2 and TLS 1.3

TLS Hash: SHA-1, SHA-256 and above

Trellix Embedded Control: Enhanced Security

Common User Data

Machine Name:	Xerox VersaLink C620 (FC:36:4B)
IPv4 Address:	10.61.16.175
Machine Serial Number:	5322980355
Machine URL:	http://10.61.16.175
Machine Activation Date:	Sep 10, 2025 21:46:30
Black Impressions:	8059
Color Impressions:	7970
Total Impressions:	16029

Machine Profile

Xerox Asset Tag:	
Customer Asset Tag:	
Service Phone Number:	
Customer Support Number:	
Supplies Phone Number:	
Recycling Phone Number:	+191-4534-456
System Administrator:	Not set
Machine Location:	machine location not set
Managed By	
Primary MB Server:	

Machine Hardware

Foreign Interface Card:	not present
Device RAM Size:	1984 MB
Device Storage Size:	used=2944MB/total=14004MB (eMMC)
EPC Memory Size:	187 MB
Productivity Kit:	Not Installed
Finisher Type:	Simple Catch Tray
Finisher Punch:	None
Finisher Folder:	not present

General Setup

Remote Services:	Enabled
Remote Software Download:	Enabled
Remote Services Trans. Time:	19:35
Xerox Workplace Cloud	Enabled
E-mail Alerts:	Disabled
Service Plan:	Metered
Geographic Region:	unknown
GMT Offset:	+05:30
Cloning Installation	Allowed (Encrypted Files Only)
File Sharing	Enabled
JBIG2	Lossless
Energy Saver	
Deep Sleep:	Disabled
Energy Saver Mode:	Job Activated
Smart Proximity Sensor	Not Available
Wake on Arrival:	
Sleep on Departure:	

Software Versions

Device Software:	123.026.005.28800
Patch Version:	None
Network Controller:	123.026.28800
UI Panel Firmware:	6.2
Marking Engine:	237.004
Finisher:	000.000.000
Machine Upgrades:	Allowed
Last Successful Upgrade:	October 22, 2025 16:14:57

Media Trays

Tray 1:	Plain, White and A4 (210 x 297 mm)
Bypass Tray:	Plain, White and A4 (210 x 297 mm)

Installed Options

PS:	Installed
-----	-----------

Connectivity

Mobile Workflows	
AirPrint Printing:	Enabled
Mopria Printing:	Enabled
Physical Connections	
USB Settings	
USB Type A Ports	All Enabled
USB Type B Port	Enabled
Wired:	Enabled
Ethernet MAC Address:	9c:93:4e:fc:36:4b
Ethernet Speed/Duplex Setting:	auto
Wireless:	Disabled
Wireless MAC Address:	
Network Name (SSID):	
BSSID:	
Security Mode:	
Encryption Algorithm:	
Status:	
Wi-Fi Direct:	Enabled
Wireless Hardware:	Not Installed
Wi-Fi Protected Setup™ (WPS) Name:	
Access Point (SSID):	
Show Password on Device Touch Screen:	
NFC:	Enabled
iBeacon (Bluetooth®) for AirPrint Di...	Enabled
iBeacon Hardware:	Not Installed
Bluetooth Device Address:	
iBeacon IP Address:	

Protocols

TCP/IPv4:	Enabled
IPv4 Address:	10.61.16.175
Subnet Mask:	255.255.255.0
Router/Gateway:	10.61.16.1
Automatic Addressing:	DHCP
DHCP Server:	
DHCP Lease Expiration:	
BOOTP Broadcast:	Disabled
Self Assigned Address State:	Enabled
Self Assigned Address:	
TCP/IPv6:	Disabled
Link Local Address:	
Use Router Supplied Prefix:	
Stateless Global Address 1:	
Stateless Global Address 2:	
Manual Address:	
DHCP Addressing:	
DHCP Address:	
Default Gateway:	
DUID (DHCP Unique Identifier):	
DNS Settings:	
Requested Host Name:	XR9C934EFC364B
Verified Host Name:	
Requested Domain Name:	
Verified Domain Name:	
Multicast DNS:	Enabled
Release DHCP Leases and DNS Registrati...	Disabled
Primary DNS Server:	10.61.7.16
Prefer IPv6 DNS over IPv4:	Enabled
Bonjour:	
Bonjour Printer Name:	Xerox VersaLink C620 (FC:36:4B)
HTTP:	Enabled
Force Traffic over Secure Connection (H...	No
IPP	Enabled
SNMP	
SNMP v1/v2:	Enabled
SNMP v3:	Disabled
LPR/LPD:	Enabled
Raw IP Printing:	Enabled
LDAP	
LDAP Server 1 Primary LDAP Address:	0.0.0.0:389
LDAP Server 1 Search Directory Root:	
LDAP Server 1 Secure Connection (LDA...	Disabled
LDAP Server 1 Validate Server Certificate...	Disabled
SMTP	
SMTP Server:	0.0.0.0:25
Connect Encryption (TLS):	No Encryption
Validate Server Certificate (TLS):	